



**MODULAR JACKS AND PLUGS: GLX Series**  
Right Angle Modular Jack

**Product Features**

- 0.570" Height
- Snap-In Board Retention Tabs
- Available in 4, 6, 8 and 10 Position Housings
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

**Performance Specifications**

**Materials and Finish**

- Housing Material**  
PBT Thermoplastic, UL 94V-0 Rated
- Contact Material**  
Phosphor Bronze

**Electrical Characteristics**

- Insulation Resistance**  
500 Megohms Min.
- Dielectric Withstanding Voltage**  
1000V RMS, 60Hz
- Contact Resistance**  
20 milliohms Max.
- Current Rating**  
1.5A
- Voltage Rating**  
125V DC


Generated Part Number

**GLX-A-44**

Part Number Builder

GLX	-	A	44	
Series		Shield Option	Positions & Contacts	Other Option

**Series**

GLX - Right Angle Modular Jack

**Shield Options**

- A - Non-Shielded with Panel Stops
- N - Non-Shielded without Panel Stops

**Number of Positions / Contacts**

- 44 - 4 Positions / 4 Contacts
- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts

**Other Option**

**Plating Option**

- Gold Flash
- 50µ" Gold Plating

**Color Option**

- Gray
- Black

Contact Kycon for High Temperature and Other Options

**GLX Series**

Dimensions in mm

**GLX-A-44xx**

