

SACC-DSI-M12FS-5P-M16XL/1,5 - Device connector, rear mounting



1416341

<https://www.phoenixcontact.com/us/products/1416341>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector, rear mounting, 5-position, coding: A , on free cable end, Rear mounting, M16 x 1.5, Individual wires, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1239115

Commercial data

Item number	1416341
Packing unit	1 pc
Minimum order quantity	50 pc
Sales key	AB24
Product key	ABQCHB
GTIN	4055626071923
Weight per piece (including packing)	59 g
Weight per piece (excluding packing)	42.27 g
Customs tariff number	85444290
Country of origin	DE

SACC-DSI-M12FS-5P-M16XL/1,5 - Device connector, rear mounting



1416341

<https://www.phoenixcontact.com/us/products/1416341>

Technical data

Notes

General	Lock nut is included in the scope of delivery
Safety note	<p>WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none">• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.• The products are suitable for applications in plant, controller, and electrical device engineering.• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.• Assembled products may not be manipulated or improperly opened.• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).• When using the product in direct connection with third-party manufacturers, the user is responsible.• For operating voltages > 50 V AC, conductive connector housings must be grounded• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.• Observe the corresponding technical data. You will find information:<ul style="list-style-type: none">o On the producto On the packing labelo In the supplied documentationo Online at phoenixcontact.com/products under the product• Only use tools recommended by Phoenix Contact• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products• Ensure that the protective or functional ground has been properly connected.• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector

SACC-DSI-M12FS-5P-M16XL/1,5 - Device connector, rear mounting



1416341

<https://www.phoenixcontact.com/us/products/1416341>

• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

Mounting

Mounting type	Rear mounting M16 x 1.5
Connection method	Individual wires

Product properties

Product type	Circular connectors (device side)
Number of positions	5
Coding	A
Thread type	M12

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Electrical properties

Rated surge voltage	1.5 kV AC
Nominal voltage U_N	60 V
Nominal current I_N	4 A

Connection data

Conductor connection

Connection method	Individual wires
Contact connection type	Socket
Conductor cross section	0.34

Connector

Connection 2

Head design	free cable end
-------------	----------------

Cable/line

Cable length	1.5
--------------	-----

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-25 ... -85

Standards and regulations

Standards/specifications	according to IEC 61076-2-101
--------------------------	------------------------------

SACC-DSI-M12FS-5P-M16XL/1,5 - Device connector, rear mounting



1416341

<https://www.phoenixcontact.com/us/products/1416341>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1416341>



EAC

Approval ID: B.01687



cULus Recognized

Approval ID: E221474-20140616

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	4 A	22 - 20	-

SACC-DSI-M12FS-5P-M16XL/1,5 - Device connector, rear mounting



1416341

<https://www.phoenixcontact.com/us/products/1416341>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-DSI-M12FS-5P-M16XL/1,5 - Device connector, rear mounting



1416341

<https://www.phoenixcontact.com/us/products/1416341>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com