



Specification:
 1. Electrical Char
 Insulation Resistance: 500MΩ min, 500V DC for 1 minute
 Contact Resistance: 20mΩ max.
 Rating Current: 1.5A max.
 Rating Voltage: 120V AC
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

2. Physical Char
 Housing: PBT Glass filled (UL 94V-0) Color: Black
 Soldering Temperature: 235°C for 5 sec.
 Spring Wire: 0.45mm Dia Phosphor Bronze
 6u" Gold plating over Nickel
 Temperature Range: -40°C to +85°C
 Durability: 550 mating cycles min.

3. Packing: Tray

RoHS compliant
 Unit:mm

| Scale | Free | | | | | |
|-----------|--------|--------------|---|-------|----------|------------|
| TOLERANCE | | | | | | |
| .XX | ±0.20 | | | | Drawn | 04.08.2016 |
| .XXX | ±0.13 | | | | Approved | 04.08.2016 |
| .XXXX | ±0.05 | | | | | |
| DIM | TOL | | | | | |
| Angle | +0°30' | Id. | ① | Drawn | Winnie | 04.08.2016 |
| | | Modification | | | | |
| | | Date | | | | |
| | | Name | | | | |

| Customer-No. | Name | Date | Name |
|--------------|--------|------------|--------|
| | Winnie | 04.08.2016 | Winnie |
| | Winnie | 04.08.2016 | Winnie |

ASSMANN WSW-No. A-2004-0-4-LP-N-R

Drawing-No. ASS 7318 CO rev00

Replace SHEET



| | | | | | | |
|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| H | G | F | E | D | C | B |
| H | G | F | E | D | C | B |