

## Power cable - PLD E 608-CA-MS/0,6/FS AM - 2702303

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Power cable, 3-position, PVC, orange RAL 2004, Plug straight, coding: black, on Socket straight, cable length: 0.6 m

### Product Description

The cable serves to connect multiple 600 class PLD enclosure lights in series.

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 112282
GTIN	4055626112282
Weight per Piece (excluding packing)	100.000 g
Custom tariff number	85444290
Country of origin	Germany

### Technical data

#### Dimensions

Length of cable	0.6 m
-----------------	-------

#### Ambient conditions

Ambient temperature (operation)	-5 °C ... 40 °C
Degree of protection	IP20
	IP40 (plugged in)

#### General

Rated current at 40°C	16 A
Rated voltage	250 V AC

## Power cable - PLD E 608-CA-MS/0,6/FS AM - 2702303

### Technical data

#### General

Number of positions	3
Insertion/withdrawal cycles	100

#### Material

Material, knurls	not available
------------------	---------------

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27060311
eCl@ss 11.0	27060311
eCl@ss 5.0	27049000
eCl@ss 5.1	27049000
eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 9.0	27060311

#### ETIM

ETIM 6.0	EC001855
ETIM 7.0	EC001855

#### UNSPSC

UNSPSC 13.2	31251501
UNSPSC 19.0	31251501
UNSPSC 20.0	31251501
UNSPSC 21.0	31251501

### Accessories

#### Accessories

Power distributor

## Power cable - PLD E 608-CA-MS/0,6/FS AM - 2702303

### Accessories

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.

---

---