

Marker cards - SK 2.5/2.8: SO (CUSTOM PRTNG) - 0804879


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Marker cards, white, Mounting type: Adhesive, For terminal block width: 2.54 mm

The illustration shows version SK 2,54/2,8 CONSEC.NOS

Key commercial data

| | |
|--------------------------------------|--------------------------------------------------------------------------------------------------------|
| Packing unit | 1 |
| Minimum order quantity | 10 |
| Catalog page | Page 500 (CL-2009) |
| GTIN |  4 017918 126100 |
| Weight per Piece (excluding packing) | 0.24 GRM |
| Country of origin | BELGUIM |

Technical data

General

| | |
|---------------------------------|-----------------------------------------------------|
| Note | Please specify the required marking with order. |
| Note | A maximum of 2 characters per position are possible |
| Height | 2.8 mm |
| Color | white |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Components | free from silicone and halogen |
| Pitch | 2.54 mm |
| Material | Polyester |
| Pitch | 2.54 mm |

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 4.0 | 24190208 |
| eCl@ss 4.1 | 24190208 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27149103 |

Marker cards - SK 2.5/2.8: SO (CUSTOM PRTNG) - 0804879

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 6.0 | 27149103 |
|------------|----------|

etim

| | |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |

unspsc

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Accessories

Accessories

Marking

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm