

Data sheet | Item number: 753-602

Power Supply; 24 VDC

[www.wago.com/753-602](http://www.wago.com/753-602)



### Item description

This supply module provides the I/O modules with the corresponding supply potential.

The maximum current provided by the supply module is 10 A. When configuring the system, the total current must not be exceeded.

Should higher currents be necessary, an intermediate supply module must be added to the assembly.

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Data Notes

|      |  |
|------|--|
| Note | Pluggable connectors and coding fingers (753 Series) are not included. |
|------|--|

## Technical data

|   |  |
|---|--|
| Signal type                                       | Voltage  |
| Signal type (voltage)                             | 24 VDC   |
| Supply voltage (system)                           | 5 VDC; via data contacts   |
| Supply voltage (field)                            | 24 VDC (-25 ... +30 %); Via power jumper contacts (power supply via CAGE CLAMP® connection; transmission via spring contact) |
| Indicators  | LED (C) green: operating voltage status: power jumper contacts   |
| Number of outgoing power jumper contacts          | 3  |
| Current carrying capacity (power jumper contacts) | 10 A   |

## Connection data

|                                     |  |
|-------------------------------------|--|
| Connection technology: field supply | 6 x CAGE CLAMP®                              |
| Connection type 1                   | Field supply                                 |
| Solid conductor                     | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Fine-stranded conductor             | 0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG |
| Strip length                        | 9 ... 10 mm / 0.35 ... 0.39 inches           |

## Physical data

|                                   |                        |
|-----------------------------------|------------------------|
| Width                             | 12 mm / 0.472 inches   |
| Height                            | 100 mm / 3.937 inches  |
| Depth                             | 69.8 mm / 2.748 inches |
| Depth from upper-edge of DIN-rail | 62.6 mm / 2.465 inches |

## Mechanical Data

|                     |             |
|---------------------|-------------|
| Mounting type       | DIN-35 rail |
| Pluggable connector | Pluggable   |

## Material Data

|                  |                              |
|------------------|------------------------------|
| Housing material | Polycarbonate; polyamide 6.6 |
|------------------|------------------------------|

Subject to changes. Please also observe the further product documentation!



|                    |          |
|--------------------|----------|
| Fire load          | 1.032 MJ |
| Weight             | 36.5 g   |
| Conformity marking | CE       |

### Environmental requirements

|  |                                       |
|--|---------------------------------------|
| Ambient temperature (operation)  | 0 ... +55 °C                          |
| Ambient temperature (storage)  | -25 ... +85 °C                        |
| Protection type  | IP20                                  |
| Pollution degree   | 2 per IEC 61131-2                     |
| Operating altitude   | 0 ... 2000 m / 0 ... 6562 ft          |
| Mounting position  | horizontal (standing/lying); vertical |
| Relative humidity (without condensation)   | 95 %                                  |
| Vibration resistance   | 4g per IEC 60068-2-6                  |
| Shock resistance   | 15g per IEC 60068-2-27                |
| EMC immunity to interference   | per EN 61000-6-2, marine applications |
| EMC emission of interference   | per EN 61000-6-4, marine applications |
| Exposure to pollutants   | Per IEC 60068-2-42 and IEC 60068-2-43 |
| Permissible H <sub>2</sub> S contaminant concentration at a relative humidity 75 % | 10 ppm                                |
| Permissible SO <sub>2</sub> contaminant concentration at a relative humidity 75 %  | 25 ppm                                |

### Commercial data

|                       |                 |
|-----------------------|-----------------|
| Product Group         | 15 (I/O System) |
| eCl@ss 10.0           | 27-24-26-10     |
| eCl@ss 9.0            | 27-24-26-10     |
| ETIM 8.0              | EC001600        |
| ETIM 7.0              | EC001600        |
| Recupel Type          |                 |
| PU (SPU)              | 1 pcs           |
| Packaging type        | box             |
| Country of origin     | DE              |
| GTIN                  | 4045454394608   |
| Customs tariff number | 85389091890     |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



## Environmental Product Compliance

|   |  |
|---|--|
| CAS-No.                                   | 25550-51-0<br>7439-92-1                                |
| REACH Candidate List Substance            | 4-Methyl-1,2-cyclohexanedicarboxylic anhydride<br>Lead |
| RoHS Compliance Status                    | Compliant,With Exemption                               |
| RoHS Exemption                            | 6(c)<br>7(a)<br>7(c)-I<br>7(c)-II                      |
| SCIP notification number (Austria)        | 6ba2c5ff-0859-4495-b7f5-2f341d961483                   |
| SCIP notification number (Belgium)        | 54966c53-b946-4ad6-b499-7c838e430680                   |
| SCIP notification number (Bulgaria)       | eed1d47b-432e-4612-a924-3f75e7b85582                   |
| SCIP notification number (Czech Republic) | cb705837-230c-4961-884d-1b7ab34fd443                   |
| SCIP notification number (Denmark)        | 975f4548-9869-4812-b5e3-b375e6e0f920                   |
| SCIP notification number (Finland)        | d480760d-1b92-4160-ba8d-988cd4a6a2c8                   |
| SCIP notification number (France)         | 7ebb22eb-9911-4188-818d-5d29b6aea1a4                   |
| SCIP notification number (Germany)        | fa9708f5-eab6-44c7-ad3e-89f917bd629c                   |
| SCIP notification number (Hungary)        | 881d2539-3155-44ef-92a5-a5a54375bde4                   |
| SCIP notification number (Italy)          | b0a54ccd-c2dc-4c61-8bd9-9818372560f9                   |
| SCIP notification number (Netherlands)    | c1572afc-e307-4051-b980-afb7c0e2abf2                   |
| SCIP notification number (Poland)         | 4a170c60-7ce4-4284-861a-594496d65dbd                   |
| SCIP notification number (Romania)        | 3bad4e0e-ced9-43ba-a149-f101192f5ddb                   |
| SCIP notification number (Sweden)         | 47ed4ecc-d177-4d78-9df0-47bc611ce976                   |

## Approvals / Certificates

### General approvals

| Logo | Approval                                      | Additional Approval Text | Certificate name            |
|------|---|--------------------------|-----------------------------|
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle | TP TC 020/2011           | EAC RU C-DE.AM02.B.00087/19 |
|      | <b>KC</b><br>National Radio Research Agency   | Article 58-2, Clause 3   | MSIP-REM-W43-SPP750         |

### Declarations of conformity and manufacturer's declarations

Certificate

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



| Logo | Approval  | Additional Approval Text | name |
|------|---|--------------------------|------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -    |
|      | <b>UK-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -    |

**Approvals for marine applications**

| Logo | Approval   | Additional Approval Text        | Certificate name  |
|------|--|---------------------------------|-------------------|
|      | <b>ABS</b><br>American Bureau of Shipping                    | -                               | 22-2219060        |
|      | <b>BSH</b><br>Bundesamt fuer Seeschifffahrt und Hydrographie | -                               | 1104              |
|      | <b>BV</b><br>Bureau Veritas S.A.                             | Rules for class. of Steel Ships | 66711/A0          |
|      | <b>DNV</b><br>DNV GL SE                                      | DNV-CG-0339,Aug.2021            | TAA0000194        |
|      | <b>KR</b><br>Korean Register of Shipping                     | -                               | KR HMB05880-AC001 |
|      | <b>LR</b><br>Lloyds Register EMEA                            | -                               | LR22180952TA      |
|      | <b>PRS</b><br>Polski Rejestr Statków                         | -                               | TE/2236/880590/19 |
|      | <b>RINA</b><br>RINA Germany GmbH                             | -                               | ELE343521XG001    |

**Approvals for hazardous areas**

| Logo | Approval  | Additional Approval Text | Certificate name                                 |
|------|---|--------------------------|--|
|      | <b>ATEX</b><br>TUEV Nord Cert GmbH                                | EN 60079-0               | TUEV14ATEX148929X (II 3 G Ex ec IIC T4 Gc)       |
|      | <b>CCCEX</b><br>CQST/CNEx   | CNCA-C23-01              | 2020312310000213 (Ex ec IIC T4 Gc)               |
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle                     | TP TC 012/2011           | EAC RU C-DE.AM02.B.00163/19 (2Ex nA IIC T4 Gc X) |
|      | <b>IECEX</b><br>TUEV Nord Cert GmbH                               | IEC 60079-0              | IECEX TUN 14.0035 X (Ex ec IIC T4 Gc)            |
|      | <b>INMETRO</b><br>TÜV Rheinland do Brasil Ltda.                   | IEC 60079-0              | BR-Ex_TÜV 12.1297 X                              |
|      | <b>UKEx</b><br>WAGO GmbH & Co. KG                                 | EN 60079-0               | UKCA_WAGO22UKEX003X_ec                           |
|      | <b>UL</b><br>Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS) | UL 121201                | E198726 Sec.1                                    |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



## Required accessories

### Pluggable connector

Male connector/plug

**Item no.: 753-110**  
Plug

[www.wago.com/753-110](http://www.wago.com/753-110)

## Optional accessories

### Shield termination

Shield clamping saddles

**Item no.: 790-116**  
Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm

[www.wago.com/790-116](http://www.wago.com/790-116)

**Item no.: 790-124**  
Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm

[www.wago.com/790-124](http://www.wago.com/790-124)

**Item no.: 790-108**  
Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm

[www.wago.com/790-108](http://www.wago.com/790-108)

**Item no.: 790-140**  
Shield clamping saddle; diameter of compatible conductor

[www.wago.com/790-140](http://www.wago.com/790-140)

**Item no.: 790-216**  
Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm

[www.wago.com/790-216](http://www.wago.com/790-216)

**Item no.: 790-220**  
Shield clamping saddle; 30 mm wide; 6 ... 20 mm

[www.wago.com/790-220](http://www.wago.com/790-220)

**Item no.: 790-208**  
Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm

[www.wago.com/790-208](http://www.wago.com/790-208)

### System housing

System enclosure

**Item no.: 850-814/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate

[www.wago.com/850-814/002-000](http://www.wago.com/850-814/002-000)

**Item no.: 850-815/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate

[www.wago.com/850-815/002-000](http://www.wago.com/850-815/002-000)

**Item no.: 850-816/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate

[www.wago.com/850-816/002-000](http://www.wago.com/850-816/002-000)

**Item no.: 850-817/002-000**  
IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate

[www.wago.com/850-817/002-000](http://www.wago.com/850-817/002-000)

Subject to changes. Please also observe the further product documentation!



|   |  |
|---|--|
| <b>Item no.: 850-825</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20                                      | <a href="http://www.wago.com/850-825">www.wago.com/850-825</a>                 |
| <b>Item no.: 850-826</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip                 | <a href="http://www.wago.com/850-826">www.wago.com/850-826</a>                 |
| <b>Item no.: 850-827</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip                 | <a href="http://www.wago.com/850-827">www.wago.com/850-827</a>                 |
| <b>Item no.: 850-827/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip         | <a href="http://www.wago.com/850-827/002-000">www.wago.com/850-827/002-000</a> |
| <b>Item no.: 850-826/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip         | <a href="http://www.wago.com/850-826/002-000">www.wago.com/850-826/002-000</a> |
| <b>Item no.: 850-828/002-000</b><br>IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip        | <a href="http://www.wago.com/850-828/002-000">www.wago.com/850-828/002-000</a> |
| <b>Item no.: 850-828</b><br>IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip                | <a href="http://www.wago.com/850-828">www.wago.com/850-828</a>                 |
| <b>Item no.: 850-834</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20                                      | <a href="http://www.wago.com/850-834">www.wago.com/850-834</a>                 |
| <b>Item no.: 850-835</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip                 | <a href="http://www.wago.com/850-835">www.wago.com/850-835</a>                 |
| <b>Item no.: 850-836</b><br>IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip                 | <a href="http://www.wago.com/850-836">www.wago.com/850-836</a>                 |
| <b>Carrier rail</b>   |  |
| Mounting accessories  |  |
| <b>Item no.: 210-197</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored                | <a href="http://www.wago.com/210-197">www.wago.com/210-197</a>                 |
| <b>Item no.: 210-198</b><br>Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored           | <a href="http://www.wago.com/210-198">www.wago.com/210-198</a>                 |
| <b>Item no.: 210-504</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored   | <a href="http://www.wago.com/210-504">www.wago.com/210-504</a>                 |
| <b>Item no.: 210-505</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored | <a href="http://www.wago.com/210-505">www.wago.com/210-505</a>                 |
| <b>Item no.: 210-506</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored  | <a href="http://www.wago.com/210-506">www.wago.com/210-506</a>                 |

Subject to changes. Please also observe the further product documentation!



|  |  |
|--|--|
| <b>Item no.: 210-508</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored         | <a href="http://www.wago.com/210-508">www.wago.com/210-508</a>                   |
| <b>Item no.: 210-113</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored                  | <a href="http://www.wago.com/210-113">www.wago.com/210-113</a>                   |
| <b>Item no.: 210-118</b><br>Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored                 | <a href="http://www.wago.com/210-118">www.wago.com/210-118</a>                   |
| <b>Item no.: 210-112</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored | <a href="http://www.wago.com/210-112">www.wago.com/210-112</a>                   |
| <b>Item no.: 210-114</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored                   | <a href="http://www.wago.com/210-114">www.wago.com/210-114</a>                   |
| <b>Item no.: 210-115</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored | <a href="http://www.wago.com/210-115">www.wago.com/210-115</a>                   |
| <b>Item no.: 210-196</b><br>Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored               | <a href="http://www.wago.com/210-196">www.wago.com/210-196</a>                   |
| <b>Pluggable connector</b>   |  |
| Coding   |  |
| <b>Item no.: 753-150</b><br>753 Series coding elements   | <a href="http://www.wago.com/753-150">www.wago.com/753-150</a>                   |
| <b>Marking accessories</b>   |  |
| Marker carrier   |  |
| <b>Item no.: 750-103</b><br>Group marker carrier   | <a href="http://www.wago.com/750-103">www.wago.com/750-103</a>                   |
| Marker   |  |
| <b>Item no.: 2009-145/000-006</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue      | <a href="http://www.wago.com/2009-145/000-006">www.wago.com/2009-145/000-006</a> |
| <b>Item no.: 2009-145</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white             | <a href="http://www.wago.com/2009-145">www.wago.com/2009-145</a>                 |
| <b>Item no.: 2009-145/000-002</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow    | <a href="http://www.wago.com/2009-145/000-002">www.wago.com/2009-145/000-002</a> |
| <b>Item no.: 2009-145/000-007</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray      | <a href="http://www.wago.com/2009-145/000-007">www.wago.com/2009-145/000-007</a> |
| <b>Item no.: 2009-145/000-005</b><br>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red       | <a href="http://www.wago.com/2009-145/000-005">www.wago.com/2009-145/000-005</a> |

Subject to changes. Please also observe the further product documentation!





|   |   |
|---|---|
| <p><b>Item no.: 2009-145/000-012</b><br/>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange</p> | <p><a href="http://www.wago.com/2009-145/000-012">www.wago.com/2009-145/000-012</a></p> |
| <p><b>Item no.: 2009-145/000-023</b><br/>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green</p>  | <p><a href="http://www.wago.com/2009-145/000-023">www.wago.com/2009-145/000-023</a></p> |
| <p><b>Item no.: 2009-145/000-024</b><br/>Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet</p> | <p><a href="http://www.wago.com/2009-145/000-024">www.wago.com/2009-145/000-024</a></p> |
| <p><b>Item no.: 248-501/000-006</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue</p>                                    | <p><a href="http://www.wago.com/248-501/000-006">www.wago.com/248-501/000-006</a></p>   |
| <p><b>Item no.: 248-501/000-007</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray</p>                                    | <p><a href="http://www.wago.com/248-501/000-007">www.wago.com/248-501/000-007</a></p>   |
| <p><b>Item no.: 248-501/000-002</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow</p>                                  | <p><a href="http://www.wago.com/248-501/000-002">www.wago.com/248-501/000-002</a></p>   |
| <p><b>Item no.: 248-501/000-012</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange</p>                                  | <p><a href="http://www.wago.com/248-501/000-012">www.wago.com/248-501/000-012</a></p>   |
| <p><b>Item no.: 248-501</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white</p>   | <p><a href="http://www.wago.com/248-501">www.wago.com/248-501</a></p>                   |
| <p><b>Item no.: 248-501/000-017</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green</p>                             | <p><a href="http://www.wago.com/248-501/000-017">www.wago.com/248-501/000-017</a></p>   |
| <p><b>Item no.: 248-501/000-005</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red</p>                                     | <p><a href="http://www.wago.com/248-501/000-005">www.wago.com/248-501/000-005</a></p>   |
| <p><b>Item no.: 248-501/000-024</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet</p>                                  | <p><a href="http://www.wago.com/248-501/000-024">www.wago.com/248-501/000-024</a></p>   |
| <p><b>Item no.: 248-501/000-023</b><br/>Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green</p>                                   | <p><a href="http://www.wago.com/248-501/000-023">www.wago.com/248-501/000-023</a></p>   |
| <p><b>Item no.: 750-100</b><br/>Marker card; as a DIN A4 sheet; plain</p>   | <p><a href="http://www.wago.com/750-100">www.wago.com/750-100</a></p>                   |
| <p>Group marker carrier</p>   |   |
| <p><b>Item no.: 750-106</b><br/>Group marker carrier</p>  | <p><a href="http://www.wago.com/750-106">www.wago.com/750-106</a></p>                   |

Subject to changes. Please also observe the further product documentation!



## Downloads

### Documentation

#### Manual

|  |                         |               |          |
|--|-------------------------|---------------|----------|
| System Manual WAGO I/O System 750/753<br>Decentralized Automation Technology | V 3.3.3<br>2023 年8月29 日 | pdf<br>8.7 MB | Download |
| Product Manual 24 V DC<br>passive  | V 1.2.0                 | pdf<br>2.0 MB | Download |
| System Manual Series 750/753<br>Online HTML                                  |                         | URL           | Download |

#### Bid Text

|                        |              |                |          |
|------------------------|--------------|----------------|----------|
| 753-602<br>X81 - Datei | 2019 年2月19 日 | xml<br>4.0 kB  | Download |
| 753-602<br>doc - Datei | 2017 年10月6 日 | doc<br>25.1 kB | Download |

#### Instruction Leaflet

|  |              |                 |          |
|--|--------------|-----------------|----------|
| CCC Ex (Additional information)<br>WAGO-I/O-SYSTEM *750-****/* | 2023 年4月26 日 | pdf<br>163.6 kB | Download |
|--|--------------|-----------------|----------|

#### Additional Information

|   |                         |               |          |
|---|-------------------------|---------------|----------|
| Disposal and Recycling<br>Electrical and electronic equipment, Batteries, Packaging | V 1.1.0<br>2022 年8月18 日 | pdf<br>2.2 MB | Download |
|---|-------------------------|---------------|----------|

#### System Description

|   |  |                 |          |
|---|--|-----------------|----------|
| Overview on WAGO-I/O-SYSTEM 750 approvals               |  | pdf<br>223.5 kB | Download |
| 750/753 Series I/O-System – General Product Information |  | pdf<br>976.2 kB | Download |

## CAD/CAE-Data

### CAD data

2D/3D Models 753-602

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



[URL](#)      [Download](#)

---

#### CAE data

WSCAD Universe 753-602

[URL](#)      [Download](#)

ZUKEN Portal 753-602

[URL](#)      [Download](#)

EPLAN Data Portal 753-602

[URL](#)      [Download](#)

---

#### Environmental Product Compliance

##### Compliance Search

Environmental Product Compliance 753-602

[URL](#)      [Download](#)

Power Supply; 24 VDC

---

#### Installation Notes

#### Product family

**WAGO I/O System 750/753**

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.