



PCE Americas Inc.  
711 Commerce Way  
Suite 8  
Jupiter  
FL-33458  
USA  
From outside US: +1  
Tel: (561) 320-9162  
Fax: (561) 320-9176  
info@pce-americas.com

PCE Instruments UK Ltd.  
Units 12/13  
Southpoint Business Park  
Ensign way  
Hampshire / Southampton  
United Kingdom, SO31 4RF  
From outside UK: +44  
Tel: (0) 2380 98703 0  
Fax: (0) 2380 98703 9  
info@pce-instruments.com

[www.pce-instruments.com/english](http://www.pce-instruments.com/english)  
[www.pce-instruments.com](http://www.pce-instruments.com)

## Technical Thermometer PCE-HPT 1

### Thermometer with Microprocessor PCE-HPT 1

1-channel thermometer with 4-wire class A Pt100 sensor / software for transmission and data value / internal data logger

The Thermometer with microprocessor is a high precision 1-channel temperature gauge. The Thermometer with microprocessor is ideal for use with various Pt100 sensors. BDue to the fact that it uses 4-wire technology has a very fast response time and precision. Therefore, the sensors of the Thermometer with microprocessor are ideal for all processes that require precision and quick response. The temperature range of the Thermometer with microprocessor reaches of  $-100$  to  $+400$  ° C. The comprehensive software and easy to use Thermometer with the microprocessor allows a simple assessment and see the values of a real-time measurement. The internal clock with date and time allows the user to accurately assign the results. The Thermometer has an internal data logger with adjustable measuring range.

- 1 channel temperature Recorder
- Automatic shutdown
- High accuracy
- Backlight
- Software included
- Internal data logger
- Internal Clock
- class A, 4-wire. Pt100 sensor
- Data-Hold Function
- Selectable units (° C / ° F)

### Technical Specifications

Sensors	Measurement range
Measurement range	$-100 \dots +400$ °C
Accuracy	$\pm 0,05$ % + $0,1$ °C (between $18$ °C y $28$ °C) just the device
Resolution	$0,01$ °C

Sensor	class A, 4-wire. Pt100 sensor
Display	5 positions, LCD
Data transmission	USB
Reproducibility	a measurement value every 0.5 s
Power supply	1x 9V battery or network adapter (optional)
Dimensions	185 x 65 x 36 mm
Weight	360 g,
Operating conditions	0 ... 60 °C, 80% R.H.
Storage conditions	-10 ... 60 °C, 80% R.H.

#### Delivery content

- 1 x Thermometer PCE-HPT 1 with microprocessor
- 1 x Pt100 sensor
- 1 x USB cable
- 1 x software,
- 1 x 9V battery
- 1 x user's manual