# 9001KY195 **SECURITY CONTROL STATION 600VAC 15A**





Main	
Range of Product	Harmony 9001K
Product or Component Type	Security control station
Device short name	9001KY
Lock type	Complete with core, 7 tumbler pins

# Complementary

Size	30 mm	
Enclosure/cubicle description	Surface mounting	
Enclosure Material	Cast Aluminium	
Type of Installation	Indoor/outdoor	
Control station composition	1 key selector switch, spring return OPEN-CLOSE	
Type of Keylock	Best	
Key withdrawal position	Center	
Connections - terminals	Screw clamp terminal	
[Ue] rated operational voltage	300 V	
[le] rated operational current AC	15 A	
Net Weight	3.55 lb(US) (1.61 kg)	

#### Environment

NEMA Degree of Protection	NEMA 3R
Environmental characteristic	Waterproof
Product Certifications	CE UL Listed CSA
Ambient Air Temperature for Operation	-13140 °F (-2560 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)

## Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	785901347460	
Nbr. of units in pkg.	1	
Package weight(Lbs)	3.75 lb(US) (1.701 kg)	
Returnability	No	
Country of origin	MX	

### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	11.43 in (29.032 cm)	
Package 1 width	4.50 in (11.43 cm)	
Package 1 Length	29.03 in (73.742 cm)	

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	<sup>₫</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫ŶYes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty	18 months