

28165.7 PVC-TAA 7X20 K WH

Device and installation marker, Length: 20 mm, Width: 7 mm, Colour: White

RAL: 9010

Business data

Article number	28165.7
Article name	PVC-TAA 7X20 K WH
GTIN (EAN)	4044211213626
For manufacturer type	Siemens Sirius
Packaging unit	600
Quantity unit	PC
Number of markers per card	60 ST
Weight per piece (not including packaging)	0.3 g
Weight per piece (including packaging)	0.3 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28165.7
Product description	Device and installation marker

Technical data

Dimensions

Length	20 mm
Width	7 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	179

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Media

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST
