

0.25 METER LENGTH



Connector A  
132122  
SMA Plug Right Angle  
Brass Gold + Heatshrink

50 Ohm RG-58  
Continuity/Hi-Pot

Connector B  
031-2367  
TNC Plug Straight  
Brass Nickel + Heatshrink

**Assembly & Label Notes**

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink  
Assembly shall be built with SN96.5 LEAD FREE solder.  
See Routing Notes for additional assembly & testing instructions.

| Connector A              |                              | Cable               |                   | Connector B              |                         |
|--------------------------|------------------------------|---------------------|-------------------|--------------------------|-------------------------|
| <b>Part #:</b>           | 132122                       | <b>Part #:</b>      | RG-58             | <b>Part #:</b>           | 031-2367                |
| <b>Description:</b>      | SMA R/A PLUG RG58 LMR195 500 | <b>Description:</b> | RG-58 - PE 0.196  | <b>Description:</b>      | TNC PLUG RG58 RG141 500 |
| <b>Type:</b>             | SMA                          | <b>Dielectric:</b>  | PE                | <b>Type:</b>             | TNC                     |
| <b>Gender:</b>           | Plug                         | <b>Shielding:</b>   | Braid             | <b>Gender:</b>           | Plug                    |
| <b>Body Type:</b>        | Right Angle                  | <b>Diameter:</b>    | 0.196             | <b>Body Type:</b>        | Straight                |
| <b>Contact Type:</b>     | Solder                       | <b>Impedance:</b>   | 50 Ohm            | <b>Contact Type:</b>     | Crimp                   |
| <b>Polarity:</b>         | Standard                     | <b>Sheathing:</b>   | None              | <b>Polarity:</b>         | Standard                |
| <b>Impedance:</b>        | 50 Ohm                       | <b>Testing:</b>     | Continuity Hi-Pot | <b>Impedance:</b>        | 50 Ohm                  |
| <b>Mounting:</b>         | Cable                        | <b>Length:</b>      | 0.25 Meter        | <b>Mounting:</b>         | Cable                   |
| <b>Body Material:</b>    | Brass                        |                     |                   | <b>Body Material:</b>    | Brass                   |
| <b>Body Finish:</b>      | Gold                         |                     |                   | <b>Body Finish:</b>      | Nickel                  |
| <b>IP Rating:</b>        | None                         |                     |                   | <b>IP Rating:</b>        | None                    |
| <b>Contact Material:</b> | Brass                        |                     |                   | <b>Contact Material:</b> | Brass                   |
| <b>Contact Finish:</b>   | Gold                         |                     |                   | <b>Contact Finish:</b>   | Gold                    |
| <b>Max. Freq.:</b>       | 12.4 GHz                     |                     |                   | <b>Max. Freq.:</b>       | 11 GHz                  |
| <b>Booting:</b>          | SMA Plug Right Angle         |                     |                   | <b>Booting:</b>          | TNC Plug Straight       |
|                          |                              |                     |                   | <b>Clocking:</b>         | 0°                      |



**CONTROLLED DOCUMENT - DO NOT COPY**

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:  
**SMA-RA-PL/TNC-ST-PL RG58 0.25M**

Part No:  
**Q-360550008.25M**

**UNLESS SPECIFIED**  
TOLERANCE:  
0-18 inches +/- 1/2"  
over 18" +/- 2%  
ASSEMBLY:  
CENTER LABEL IF LENGTH  
IS LESS THAN 12 INCHES

## RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Compliant).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

**Date:** 10/1/2023

**Part Number:** Q-360550008.25M

**Manufacturer:** Amphenol Custom Cable

**Description:** SMA-RA-PL/TNC-ST-PL RG58 0.25M

***This information is valid as of the date indicated for the item (part number) listed.***

**Director of Quality Assurance**

*Janice Frank*