



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939

## 2SD2257

## **Features**

- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1
- Low V<sub>CE(SAT)</sub>:V<sub>CE(SAT)</sub>=1.5V(Max.)@I<sub>C</sub>=1.5A Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix designates RoHS Compliant. See ordering information)
  Halogen free available upon request by adding suffix "-HF"

## Maximum Ratings

Symbol	Rating	Rating	Unit
$V_{CEO}$	Collector-Emitter Voltage	100	V
V <sub>CBO</sub>	Collector-Base Voltage	100	V
$V_{EBO}$	Emitter-Base Voltage	8.0	V
lc	Collector Current-Continuous	3.0	Α
Ісм	Collector Current-Peak	5.0	Α
lв	Base Current-Continuous	0.3	Α
P <sub>C</sub>	Collector power dissipation $T_A=25^{\circ}C$ $T_C=25^{\circ}C$	2.0 20	W
$T_J$	Junction Temperature	-55 to +150	°C
$T_{STG}$	Storage Temperature	-55 to +150	°C

#### Electrical Characteristics @ 25°C Unless Otherwise Specified Parameter Min Typ Max Units Symbol


OFF CHARACTERISTICS					
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage	100		Vdc	
	(l <sub>c</sub> =10mAdc, l <sub>B</sub> =0)				
I <sub>CBO</sub>	Collector-Base Cutoff Current	10 μAdc		μAdc	
	(V <sub>CB</sub> =100Vdc,				
I <sub>EBO</sub>	Emitter-Base Cutoff Current			4.0	mAdc
	(V <sub>EB</sub> =8.0Vdc,				

## **ON CHARACTERISTICS**

h <sub>FE(1)</sub>	DC Current Ga (lc=1.0Adc, V	2000				
h <sub>FE(2)</sub>	DC Current Gain (b=2.0Adc, Vc=2.0Vdc)			1	I	
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage (\( \begin{align*} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			l	1.5	Vdc
$V_{BE(sat)}$	Base-Emitter Sa (l <sub>c</sub> =1.5Adc, l <sub>f</sub>	-	-	2.0	Vdc	
V <sub>ECF</sub>	C-E Diode Forward Voltage (I <sub>F</sub> =1.0Adc)				2.0	Vdc
ton	Turn-on Time	I <sub>B1</sub> = I <sub>B2</sub> = 1.5mA;	-	0.5	-	μs
t <sub>f</sub>	Fall time	RL= $20\Omega$ ; VCC $\approx 30V$ P <sub>W</sub> = $20\mu$ s;		0.5	-	μs
t <sub>stg</sub>	Storage time	Duty Cycle≤1%		2.0		μs

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

# **NPN Silicon Power Transistors**



PIN 1.	BASE
PIN 2.	COLLECTOR
PIN 3.	EMITTER

	DIMENSIONS				
DIM	INCHES		MM		NOTE
DIIVI	MIN	MAX	MIN	MAX	NOTE
Α	.392	.408	9.96	10.36	
В	.138		3.	50	Ф
С	.1	.106		2.70	
D	.583	.598	14.80	15.20	
Е	.520		20 13.20		
F	.142	.158	3.60	4.00	
G	.1	.100		2.54	
Н	.020	.035	0.50	0.90	
J	.043	.053	1.10	1.35	
M	.169	.185	4.30	4.70	
N	.104	.126	2.65	3.20	
P	.087	.114	2.20	2.90	
Q	.020	.030	0.50	0.75	



#### **Micro Commercial Components**

## Ordering Information:

Device	Packing
Part Number-BP	Bulk;5Kpcs/Box

Note: Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.