

Product information

88 01 250

KNIPEX Alligator®

DIN ISO 8976



- good access to the workpiece due to slim size of head and joint area
- more output and comfort compared to conventional water pump pliers of the same length: 9-notch adjustment positioning for 30 % more gripping capacity
- box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- Chrome vanadium electric steel, forged, multi stage oil-hardened

Allgemein

| | |
|-------------|-------------------------------|
| Article No. | 88 01 250 |
| EAN | 4003773022992 |
| Pliers | black atramentized |
| Head | polished |
| Handles | with non-slip plastic coating |
| weight | 343 g |
| Dimensions | 250 x 92 x 50 mm |

Technische Attribute

| | |
|---------------------------------|---------|
| Adjustment positions | 9 |
| Capacities for pipes (diameter) | Ø 2 |
| Capacities for nuts | 46 mm |
| Capacities for pipes (diameter) | Ø 50 mm |

Klassifikation

| | |
|----------------|------------|
| eCl@ss 5.1.4 | 21040301 |
| ETIM 5.0 | EC000164 |
| ETIM 6.0 | EC000164 |
| proficl@ss 6.0 | AAA936c004 |

technical change and errors excepted