



## DC POWER CONNECTORS: KLDVX Series

Vertical PCB Mount DC Power Jack

### Product Features

- 2.0mm and 2.5mm
- Mounts Perpendicular to PCB
- Built in DC On/Off Switch
- CSA/NRTL Certified File No. LR78160
- UL File No. E140125

### Performance Specifications

#### Materials and Finish

- Plastic Housing:** High Temperature Thermoplastic, UL94V-0 Rated, Black Color
- Center Pin:** Brass, Nickel Plated
- Contact #1:** Brass, Matte Tin Plated
- Contact #2:** Phosphor Bronze, Matte Tin Plated
- Contact #3:** Brass, Matte Tin Plated

### Electrical Characteristics

- Contact Resistance Before Durability Test**
- Between Terminals:** 30 milliohms Max.
- Plug to Contacts:** 50 milliohms Max.
- After Durability Test**
- Between Terminals:** 60 milliohms Max.
- Plug to Contacts:** 100 milliohms Max.
- Rated Voltage:** 24V DC
- Rated Current:** 3.5A
- Insulation Resistance:** 100 Megohms Min.
- Dielectric Withstanding Voltage:** 500V AC RMS for 1 Minute


### Mechanical Characteristics

- Durability Test:** 5000 Cycles
- Insertion Force:** 0.3kg - 2.0kg
- Extraction Force:** 0.3kg - 2.0kg
- Operating Temperature:** -25°C to +85°C


Generated Part Number

**KLDVX-0202-B**

Part Number Builder



#### Series

KLDVX-0202 - Vertical PCB Mount DC Power Jack

#### Diameter

- - 2.0mm Center Pin Diameter
- - 2.5mm Center Pin Diameter

Contact Kycon For Other Options

### KLDVX-0202 Series

Dimensions in mm

