



General ordering data

Order No.	9513890000
Part designation	STB 3 S-ST1.4404
Version	Ex enclosure, 100 mm, 190 mm, 190 mm, Stainless steel 1.4404
EAN	4008190498443
Qty.	1 pc(s).

Dimensions

Fixing dimension, width	215 mm
Height	100 mm
Length	190 mm
Width	190 mm

General details

Cover fixing	4 x M6 captive (hexagon)
Enclosure fixing	8 mm holes through outside mounting
Integral fixing	TAS 20 rail welded to floor
Resistance to shocks	7 J
Sealing material	Chloroprene (cover & flange)
Version cover	closed
Colour	shiny, electropolished
Surface finish	polished, chemically immersed
Class of protection to EN 60529	IP 66
Weight	3,000 g
Ambient temperature, min.	-20 °C
Ambient temperature, max.	85 °C

Screwed cable glands top/bottom

M 12	21
M 16	12
M 20	10
M 25	4
M 32	3
M 40	2

Screwed cable glands top/bottom

Side of enclosure Top / Bottom

Screwed cable glands, left/right

M12 21

M16 19

M20 8

M25 7

M32 3

M40 2

On housing side left / right

Approvals

Approvals institutes

**Classifications**

ETIM 2.0 EC000049

ETIM 3.0 EC000049

eClass 4.1 27-14-12-06

eClass 5.0 27-18-05-02

eClass 5.1 27-18-05-02

Similar products

Order No.	Part designation	Version
3873300000	STB 1 S-ST1.4404	Ex enclosure, 80 mm, 120 mm, 120 mm, Stainless steel 1.4404
9524780000	STB 1.1 S/S	Ex enclosure, 80 mm, 150 mm, 120 mm, Stainless steel 1.4404
3873700000	STB 2 S-ST1.4404	Ex enclosure, 90 mm, 150 mm, 150 mm, Stainless steel 1.4404
9513920000	STB 4 S-ST1.4404	Ex enclosure, 120 mm, 250 mm, 250 mm, Stainless steel 1.4404
9505300000	STB 5 S-ST1.4404	Ex enclosure, 120 mm, 160 mm, 380 mm, Stainless steel 1.4404
9505310000	STB 6 S-ST1.4404	Ex enclosure, 130 mm, 250 mm, 400 mm, Stainless steel 1.4404