



www.centralsemi.com

## DESCRIPTION:

The CENTRAL SEMICONDUCTOR CJD2955 and CJD3055 are complementary silicon power transistors manufactured by the epitaxial base process, mounted in a surface mount package, and designed for high current amplifier and switching applications.

MARKING: FULL PART NUMBER


SYMBOL UNITS Collector-Base Voltage 70 VCBO V Collector-Emitter Voltage 60 V VCEO Emitter-Base Voltage 5.0 V VEBO **Continuous Collector Current** 10 А ΙC **Continuous Base Current** ΙB 6.0 А **Power Dissipation** PD 20 W Power Dissipation (T<sub>A</sub>=25°C)  $P_{D}$ 1.75 W °C Operating and Storage Junction Temperature TJ, Tstg -65 to +150 **Thermal Resistance** ΘJC 6.25 °C/W °C/W Thermal Resistance 71.4 ΘJA ELECTRICAL CHARACTERISTICS: (T<sub>C</sub>=25°C unless otherwise noted) SYMBOL **TEST CONDITIONS** UNITS MIN MAX ICEO V<sub>CF</sub>=30V 50 μΑ 20 μA V<sub>CE</sub>=70V, V<sub>BE(off)</sub>=1.5V ICEV V<sub>CE</sub>=70V, V<sub>BE(off)</sub>=1.5V, T<sub>C</sub>=150°C 2.0 mΑ ICEV 20 μA V<sub>CB</sub>=70V Ісво V<sub>CB</sub>=70V, T<sub>C</sub>=150°C 2.0 mΑ I<sub>CBO</sub>  $V_{EB}$ =5.0V 500 μA **I**EBO I<sub>C</sub>=30mA 60 BVCEO V V<sub>CE(SAT)</sub> I<sub>C</sub>=4.0A, I<sub>B</sub>=400mA 1.1 V I<sub>C</sub>=10A, I<sub>B</sub>=3.3A 8.0 V V<sub>CE</sub>(SAT) V<sub>CF</sub>=4.0V, I<sub>C</sub>=4.0A 1.8 V V<sub>BE(ON)</sub> h<sub>FE</sub> V<sub>CE</sub>=4.0V, I<sub>C</sub>=4.0A 20 100 V<sub>CE</sub>=4.0V, I<sub>C</sub>=10A hFE 5.0 V<sub>CF</sub>=10V, I<sub>C</sub>=500mA, f=1.0MHz MHz 2.0 fT

**MAXIMUM RATINGS:** (T<sub>C</sub>=25°C unless otherwise noted)


R4 (21-January 2013)



#### SURFACE MOUNT SILICON COMPLEMENTARY POWER TRANSISTORS



# DPAK CASE - MECHANICAL OUTLINE



- H -

#### LEAD CODE:

- 1) Base
- 2) Collector
- 3) Emitter
- 4) Collector
- MARKING:

FULL PART NUMBER

DIMENSIONS					
	INCHES		MILLIMETERS		
SYMBOL	MIN	MAX	MIN	MAX	
A	0.083	0.108	2.10	2.75	
В	0.016	0.032	0.40	0.81	
С	0.035	0.063	0.89	1.60	
D	0.203	0.228	5.15	5.79	
E	0.020	-	0.51	-	
F	0.018	0.024	0.45	0.60	
G	0.051	0.071	1.30	1.80	
Н	0.248	0.268	6.30	6.81	
J	0.197	0.217	5.00	5.50	
K	0.209	0.245	5.30	6.22	
L	0.025	0.040	0.64	1.02	
М	0.090	0.115	2.30	2.91	
N	0.012	0.045	0.30	1.14	
Р	0.180		4.60		
R	0.090		2.30		
			DPAK (F	REV: R0)	

R4 (21-January 2013)

www.centralsemi.com

### OUTSTANDING SUPPORT AND SUPERIOR SERVICES

#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options

#### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- · Environmental regulation compliance
- Customer specific screening
- · Up-screening capabilities

· Custom product packing

Custom bar coding for shipments

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

#### REQUESTING PRODUCT PLATING

- If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when 1. ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### CONTACT US

#### **Corporate Headquarters & Customer Support Team**

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110 Main Fax: (631) 435-1824 Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors: www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's LIMITATIONS AND DAMAGES DISCLAIMER. which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms





http://www.centralsemi.com

# Product End of Life Notification

PDN ID:	PDN01180 Rev:001
Notification Date:	10/11/21
Last Buy Date:	N/A
Last Shipment Date	N/A

Summary: The following transistors manufactured in the DPAK case are discontinued and now classified as End of Life (EOL). Revision 001, dated October 8, 2021, issued to add CJD13003 and CJD41C which were previously excluded in error.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

#### \* All Plating types (PBFREE,TIN/LEAD) for each item listed are included in this notice.

Central Part Number	Suggested Replacement
CJD112 TR13	N/A
CJD117 TR13	N/A
CJD122 BK	N/A
CJD122 TR13	N/A
CJD127 TR13	N/A
CJD13003 BK	N/A
CJD13003 TR13	N/A
CJD200 TR13	N/A
CJD2955 TR13	N/A
CJD3055 TR13	N/A
CJD31C TR13	N/A
CJD32C TR13	N/A
CJD340 TR13	N/A
CJD350 TR13	N/A
CJD41C BK	N/A
CJD41C TR13	N/A
CJD42C TR13	N/A
CJD44H11 TR13	N/A
CJD45H11 TR13	N/A
CJD47 TR13	N/A
CJD50 BK	N/A
CJD50 TR13	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.