






NOTE:ALL MATERIAL COMPLIANT ROHS STANDARD

REVISION INFORMATION


Rev.	Rev.Date	Modified By	Brief Description



PIN ASSIGNMENT(1.4v)



Label:
Size:2.45" x 1.64"



Electrical character:

- 1)100% Open/short/Intermittent testing
- 2)Withstanding voltage:DC 300V AT 10ms.
- 3)Insulation resistance:10M Ohm(min)
- 4)Residual operating current:
 - a.<1M=0.5mA; b.1.0~2.0M=1.0mA;
 - c.2.0~3.0M=2.0mA; d.3.0~5.0M=3.0mA;
 - e.5.0~10M=5.0mA; f.10~15M=7.0mA;
- 5)Conductive resistance:5 Ohm Max

NO.	PART NAME	SPECIFICATION DESCRIPTION	QT'Y	UNIT
④	Overmold	PVC,45Pa,Black	N/A	G
③	Innermold	PE,Low density	N/A	G
②	HDMI_Conn	HDMI A/M,PIN G/F,Black Insulation,Steel-Shell(G/F Plated),Solder type	2	PCS
①	Cable	UL20276 (26#BC/1P+ADM)/5C+26#BC/4C+F+A+D+B(16/6/0.12,Al-Mg)+PVC(CL2),Black,Ø8.5mm	N/A	MM

DRAWN BY		DATE: 2014/07/04	DESCRIPTION: HDMI AM TO AM Cable,26#,R T	
CHECKED BY		SHEET 1 of 1	ITEM NO. HDMIMM	
APPROVED BY	SCALE None	REV. 00	UNIT: mm	