



## Features

- Basic Protektive Pak tray
- Great container for Kanban
- Permanently static dissipative foam (shuntable) laminated to our impregnated corrugated material provides ESD and shock protection

**Foam Electrical Properties:**  $1 \times 10^4$  to  $< 1 \times 10^{11}$  ohms

**Foam Thickness:** 1/4" (+/- 1/16" tolerances)

Item	Size I.D. - L x W x D (IN)
37650	17-3/4 x 10-3/4 x 2-1/8
37651	17-7/8 x 13-5/8 x 2-1/8
37653	19-1/4 x 13-1/8 x 2-1/8
37654	19-3/8 x 15-3/4 x 2-1/8
37652	24 x 13-1/2 x 2-1/8

*Dimensional tolerances are +/- 1/8" unless otherwise specified*

**Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and worksurface standard ANSI/ESD S4.1**

## SPECIFICATIONS

### Properties

#### Surface Resistance

#### Sloughing Test

#### Recyclability

### Typical Values

$1 \times 10^6$  to  $< 1 \times 10^9$  ohms

Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.

No conductive particles abraded from surface

Complete recyclability of package

### Test Procedures/Method

ANSI/ESD STM11.11

ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load

Rockwell International Test Report of January 8, 1992

Rockwell International Test Report of January 8, 1992

### RoHS, REACH, and Conflict Minerals Statement:

See the Desco Industries ROHS, Reach and Conflict Minerals Statement  
[Descoindustries.com/ROHS3.aspx](http://Descoindustries.com/ROHS3.aspx)

See the Protektive Pak Limited Warranty  
[Protektivepak.descoindustries.com/Limited-Warranty.aspx](http://Protektivepak.descoindustries.com/Limited-Warranty.aspx)



Made in the  
United States of America

*Specifications and procedures subject to change without notice.*

## BOARD HANDLER TRAYS

**PROTEKTIVE PAK**  
BURIED SHIELDING LAYER

PROTEKTIVE PAK  
13520 MONTE VISTA AVENUE, CHINO, CA 91710  
PHONE (909) 627-2578  
[ProtektivePak.com](http://ProtektivePak.com)

**DRAWING NUMBER**  
37650

**DATE:**  
December  
2018