

General information

| | |
|-------------------|---------------------|
| Part number | G82YAR-P19UF00-000L |
| Termination | pcb |
| Size | 2 |
| Locking principle | break , push |
| Coding | a_key_amc |
| Cable Diameter | cable_amc_2 |



UV JING-A

19 JST SHRS 19 positions

PANEL CUT OUT:

DIMENSIONS:

PCB-LAYOUT:

Contact insert description

| | |
|----------------------|---------|
| Number of contacts | 19 |
| Contact type | sockets |
| Contact diameter | 07mm |
| Insulator material | peek |
| Termination | pcb |
| Termination diameter | 05mm |

reverse_gender_on_request

Technical information

| | | |
|--------------------------------|---------|---------------|
| Nominal current single contact | 05_a | iec_60512_5_2 |
| Nominal current insert | 2,25 A | vde_0298_4 |
| Test voltage | 1_kv_ac | eia_364_20f |

safety_text

Mechanical and environmental data

| | |
|-----------------------|--------------|
| Degree of protection* | ipsk8_ip6k9k |
| Operating temperature | 51_125_c |
| Mating cycles | 5000 |

mated

Material and surface treatments

| | |
|---------|---------------|
| Housing | ruthenium |
| Contact | cu_alloy_gold |

safety_text_2

ul_text

illustrative_text