



SIMATIC ET 200SP, BusAdapter: BA SCRJ/FC, media converter FOC-CU
1x SCRJ FO connection and, 1x FastConnect (FC) connection

General information	
Product type designation	BA SCRJ/FC
HW functional status	from FS04
Interfaces	
Number of PROFINET interfaces	1; 2 ports (SCRJ + FC)
Supports protocol for PROFINET IO	
<ul style="list-style-type: none"> Number of FC (FastConnect) connections Number of SCRJ ports Number of LC ports 	1 1 0
Cable length	
<ul style="list-style-type: none"> — PCF — Plastic FOC (POF) — PCF-GI — Cu conductors 	100 m 50 m 250 m 100 m
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. 	-25 °C 60 °C -25 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual
Dimensions	
Width	20 mm
Height	69.5 mm
Depth	59 mm
Weights	
Weight, approx.	50 g
last modified:	3/14/2022