



Aug.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All rights reserved.
 In case of consideration for using Automotive equipment/device which demands high reliability, kindly contact our sales window correspondents.

Applicable standard				
Rating	Operating temperature range	-35°C to + 85°C (Note 1)	Storage temperature range	-10°C to + 60°C (Note 3)
	Operating humidity range	20 % to 80 % (Note 2)	Storage humidity range	40 % to 70 % (Note 3)
	Voltage	AC/DC 100V	Applicable connector	DF50-20DP-1V (##) DF50-20DP-1H (##)
	Current 	AWG 26 : 1.0 A AWG 28 : 1.0 A AWG 30 : 0.9 A AWG 32 : 0.7 A	Applicable Contact 	DF50-26SCFA (##) DF50-2830SCFA (##) DF50K-2830SCFA (##) DF50-3032SCFA (##)

Specifications

Item	Test method	Requirements	QT	AT
------	-------------	--------------	----	----


Construction

General examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		X	X

Electric characteristics

Insulation resistance	100V DC.	500MΩ MIN.	X	-
Voltage proof	300V AC for 1 min.	No flashover or breakdown.	X	-

Mechanical characteristics


Mechanical operation 	30times insertions and extractions.	No damage, crack or looseness of parts.	X	-
Vibration	Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for each, for 3 directions.		X	-
Shock	490 m/s ² duration of pulse 11 ms At 3 times for 3 directions.		X	-

Environmental characteristics

Damp heat (Steady state)	Exposed at 40 ± 2 °c, 90 to 95 %, 96 h.	① Insulation resistance: 100MΩ MIN. ② No damage, crack or looseness of parts.	X	-
Rapid change of temperature	Temperature -55→+85°C Time 30→ 30min. Under 5 cycles. (The transferring time of the tank is 2 to 3 min)	① Insulation resistance: 500MΩ MIN. ② No damage, crack or looseness of parts.	X	-

Remarks



Note 1: Include the temperature rising by current.
 Note 2: No condensing.
 Note 3: Apply to the condition of long term storage for unused products before harness assembly.
 After harness assembly, operating temperature and humidity range is applied for interim storage during transportation.

Count	Description of revisions	Designed	Checked	Date
 3	DIS-H-00005496	HT. SATO	SZ. ONO	20191120

Unless otherwise specified, refer to IEC 60512.

	Approved	OM. MIYAMOTO	20120131
	Checked	OM. MIYAMOTO	20120131
	Designed	TT. OHSAKO	20120131
	Drawn	TT. OHSAKO	20120131

Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing no. **ELC-339520-00-00**

	Specification sheet	Part no.	DF50S-20DS-1C	
	Hirose electric co., ltd.	Code no.	CL665-0020-2-00	 1/1