



Monday, April 16, 2007

## 1520135-2 Product Details

<p>No Image Available</p>	<p>Power Toggle Switches</p> <p> <a href="#">RoHS Compliant (Statement of Compliance)</a></p> <p><b>Product Highlights:</b></p> <ul style="list-style-type: none"> <li>● Double Pole - Single Throw Configuration (Pole-Throw)</li> <li>● Toggle Length = 12.70 mm</li> <li>● Toggle Style = BALL</li> <li>● Bushing Length = 11.50 mm</li> <li>● Termination Type = Screw-In Terminal</li> </ul> <p><a href="#">View all Features</a></p>	<p><b>Quick Links</b></p> <ul style="list-style-type: none"> <li>▶ <a href="#">Check Pricing &amp; Availability</a></li> <li>▶ <a href="#">Search for Tooling</a></li> <li>▶ <a href="#">Product Feature Selector</a></li> <li>▶ <a href="#">Contact Us About This Product</a></li> </ul>
<p>Documentation &amp; Additional Information</p>		
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Catalog Pages/ Data Sheets:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>● None Available</li> </ul>	<p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">Tooling</a></li> </ul>	
<p>Product Features (Please use the Product Drawing for all design activity)</p>		
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>● Configuration (Pole-Throw) = Double Pole - Single Throw</li> <li>● Termination Type = Screw-In Terminal</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>● UL/CSA 125V Current Rating (Amps.) = 16</li> <li>● UL/CSA 250V Current Rating (Amps.) = 8</li> <li>● UL/CSA 125V Horse Power Rating (hp) = 1.00</li> </ul> <p><b>Housing Related Features:</b></p> <ul style="list-style-type: none"> <li>● Toggle Length (mm [in]) = 12.70 [0.500]</li> <li>● Toggle Style = BALL</li> </ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>● Bushing Length (mm [in]) = 11.50 [0.453]</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>● <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>● <a href="#">Lead Free Solder Processes</a> = Not reviewed for lead free solder process</li> <li>● RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>● Brand = Alcoswitch</li> </ul>	

Languages: English | [Deutsch](#) | [Español](#) | [Português \(do Brasil\)](#) | [Русский](#) | [Italiano](#) | [正體中文 \(繁體\)](#) | [中文 \(简体\)](#) | [日本語](#)  
 Country Sites: [China](#) | [Japan](#)

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Supplier](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)  
 © 2007 Tyco Electronics Corporation All Rights Reserved