



NOTES:

1. RoHS COMPLIANT
- ② 2. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
4. CONTACTS: COPPER ALLOY
PLATING: 8µin HARD GOLD over min. 50µin NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
5. CAPACITANCE: 180pF ± 20%
6. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
7. CONNECTOR IS PART MARKED: 242A26760X CONEC ABC

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
1 x b	A 3387	15.07.2009	Petker
a	Origin		
rev.	description	date	name

tolerance	dim. in mm	scale:	2:1 (5:1)	
		material:	SEE NOTES	
date	name	title: D-SUB FILTER FEMALE 25pos. SOLDER CUP		
drawn	30.06.09 Petker			
appd.	01.07.09 Fischer			
norm				
d-old		dwg no:	Inventor 10	DIN-A3
			24K1A1182	sh: 1
			part no:	242A26760X

