

Specification Sheet

Part Number: 157-00214



All-in-one bundling and fastening solution reduces costs and assembly time.

Anti-rotational oval fastener forces bundle to travel in intended direction.

Stand-off cable ties route and position bundles above a mounting hole to protect them from rubbing, heat or obstructions.

1-Pc Cable Tie/Fir Tree Mount, 25mm Offset, 9.7"L, PA46, Black, 500/bg

Article Number 157-00214

Type T50ROSFT625SO

Color Black (BK)

Quantity Per carton

Product Description One-piece stand-off cable tie and mount offers a simple bundling and mounting solution. The innovative design of this fir tree establishes a 360-degree interface with the panel hole, ensuring a more secure fit. The oval shape won't rotate once inserted, ensuring proper routing of wires and hoses. Stand-off feature positions bundles above a mounting hole. The disc prevents rattling in high-vibration applications and protects against debris ingress.

Short Description 1-Pc Cable Tie/Fir Tree Mount, 25mm Offset, 9.7"L, PA46, Black, 500/bg

Global Part Name

T50ROSFT625SO-PA46-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225.0

Length L (Imperial) 9.7

Length L (Metric) 247.2

Offset Length (Imperial) 0.98

Offset Length (Metric) 25.0

Fixation Method Fir Tree

Identification Plate Position none

Releasable Closure No

Width W (Imperial) 0.20

Width W (Metric) 5.1

Bundle Diameter Min (Imperial) 0.08

Bundle Diameter Min (Metric) 2.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

| | |
|---|----------------------|
| Thickness T (Metric) | 1.5 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.32 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 6.0 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.27 |
| Mounting Hole Diameter D (Metric) | 6.1 - 6.9 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Metric) | 6.9 |
| Disc Diameter (Metric) | 19.0 |
| Disc Diameter (Imperial) | 0.75 |
| Material | Polyamide 4.6 (PA46) |
| Material Shortcut | PA46 |
| UV Resistant (Yes/No) | No |

Operating Temperature -40°F to +266°F (-40°C to +130°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)