



**TECHNICAL**

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	120VAC
RATED CURRENT:	15A
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	90 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3000 OPERATIONS
ENCLOSURE:	NEMA 3R

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "A"	LENGTH "L"
1301530054	15052-1	9.50 IN.	1 FT 11.4 IN.
1301530067	15052-6	4 FT. 10.50 IN.	6 FT. 0.4 IN.
1301530060	15052-25	23 FT. 10.50 IN.	25 FT. 0.4 IN.
1301530064	15052-50	48 FT. 10.50 IN.	50 FT. 0.4 IN.
1301530055	15052-100	98 FT. 10.50 IN.	100 FT. 0.4 IN.

FUNCTIONAL SYMBOLS E=0 E=0 E=0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		<p style="text-align: center;"><b>molex</b></p> <p style="text-align: center;">GFCI IN-LINE 15A W/WATERTITE PLUG &amp; CONNECTOR</p>				
	DIMENSION UNITS	SCALE			CURRENT REV DESC: UPDATED TABLE AND ADDED TECHNICAL		
	INCH NTS		GENERAL TOLERANCES (UNLESS SPECIFIED)				
	ANGULAR TOL ± °		EC NO: 693149				
DIVISIONAL SYMBOLS	4 PLACES ±	DRWN: PPURSUTANDEL 2021/12/29					
	3 PLACES ±	CHKD: DNGUYEN62 2022/01/26					
	2 PLACES ±	APPR: HKNEELAND 2022/04/28					
	1 PLACE ±	INITIAL REVISION:					
0 PLACES ±	DRWN: PPURSUTANDEL 2019/07/26		DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
			B-SIZE	130153	SEE TABLE	GENERAL MARKET	1 OF 1