



# Sound Level Meter PCE-318



**Sound level meter PCE-318 with a range between 26 ... 130 dB (A) and an analog output/ recalibrated / Class II (accuracy  $\pm 1.5$  dB)**

The noise meter PCE-318 detects the volume from a sound level of 26 dB (A). The meter is ideal for measuring very low noises, for example, noises from computer fans. The class II noise meter with jumbo display (and at a very good price / performance ratio) is ideal for measurements of sound and noise in different environments, at work, condition monitoring, etc.

Also known as the phonometer, this device is designed to IEC 651 Type II and has a very high accuracy of  $\pm 1.5$  dB. Another advantage of this meter is the analogue output. This allows the connection of an external data logger / recorder for long-term recording.

- ▶ measuring range **26 ... 130 dB**
- 6 measuring ranges selectable
- ▶ analog output (AC & DC) / usable in combination with optionally available data logger (see accessories)
- ▶ memory for 99 measured values, available in the display
- ▶ frequency range 31.5 Hz to 8 kHz
- ▶ large display with bargraph
- ▶ adjustable measuring ranges on the dB meter: Low & High
- ▶ A and C frequency rating
- ▶ fast and slow time evaluation
- ▶ Min- & Max Hold function
- ▶ Tripod mounting device
- ▶ including wind noise suppressor

Subject to change



# Specifications

## Technical specifications

Measurement range	26 ... 130 dB
Level range selection	6 level ranges: 26 ... 80 dB, 30 ... 90 dB, 40 ... 100 dB, 50 ... 110 dB, 60 ... 120 dB, 70 ... 130 dB
Resolution	0.1 dB
Accuracy	±1.5 dB (ref. 94 dB at 1 kHz)
Frequency range	31.5 Hz ... 8 kHz
Time weighting	Fast and Slow
Frequency weighting	A and C
Memory	Up to 99 readings, available on the display
Output	Analog, AC / DC
Operating conditions	-10 ... +50 °C / +14 ... +122 °F, less than 90% RH
Storage conditions	-10 ... +60 °C / +14 ... +140 °F, less than 75% RH
Power	1 x 9 V battery (PP3)
Weight	Approx. 260 g / 0.57 lb
Dimensions	Approx. 264 x 68 x 27 mm / 10.39 x 2.68 x 1.06"
Standards	IEC 651 Type 2 Class 2

See user manual for complete technical specifications.

# More information

Manual



More product info



Similar products



Subject to change