


RAD-PIG-EF316-N-SMA

Order No.: 2867694



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867694>

Adapter cable, pigtail 30 cm N (female) -> SMA (male), insertion attenuation 1.5 dB at 2.4 GHz; impedance 50 ohms;

| Commercial data | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 939069 |
| sales group | H178 |
| Pack | 1 pcs. |
| Customs tariff | 85442000 |
| Catalog page information | Page 623 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
09/03/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data | |
|--------------------|---------------------------|
| General | |
| Connection 1 | Plug connector connection |
| Type of connection | Type N (female) |
| Connection 2 | Plug connector connection |
| Type of connection | Type SMA (male) |
| Fixed cable length | 30 cm |

| | |
|---------------------------------|---------------------------|
| Cable type | EF 316 |
| Cable, attenuation | approx. 1.5 dB/m |
| Minimum bending radius | 12.50 mm |
| External diameter | 2.50 mm |
| Outer sheath, material | Radox (LSFH) |
| Connection name | Plug connector connection |
| Type of connection | Type N (female) |
| Ambient temperature (operation) | -40 °C ... 70 °C |

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;