

84 INCHES LENGTH




Connector A
901-9872
SMA Plug Right Angle
Brass Gold + Heatshrink

50 Ohm RG-174
Continuity/Hi-Pot

Connector B
919-387P-51A
MCX Plug Right Angle
Brass Gold-Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.



Connector A		Cable		Connector B	
Part #:	901-9872	Part #:	RG-174	Part #:	919-387P-51A
Description:	SMA R/A PLUG RG174 500	Description:	RG-174 - PE 0.1	Description:	MCX R/A PLUG RG174 RG188 RG316 500
Type:	SMA	Dielectric:	PE	Type:	MCX
Gender:	Plug	Shielding:	Braid	Gender:	Plug
Body Type:	Right Angle	Diameter:	0.1	Body Type:	Right Angle
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder
Polarity:	Standard	Sheathing:	None	Polarity:	Standard
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Mounting:	Cable	Length:	84 Inches	Mounting:	Cable
Body Material:	Brass			Body Material:	Brass
Body Finish:	Gold			Body Finish:	Gold-Nickel
IP Rating:	None			IP Rating:	None
Contact Material:	Brass			Contact Material:	Brass
Contact Finish:	Gold			Contact Finish:	Gold
Max. Freq.:	12.4 GHz			Max. Freq.:	6 GHz
Booting:	SMA Plug Right Angle			Booting:	MCX Plug Right Angle
				Clcking:	0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-RA-PL/MCX-RA-PL G174 84I

Part No:
Q-3401A0003084I

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES