Data sheet







Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 2 A

Business data

Article number	<u>4982.0</u>
Article name	SI 6,3x32 2,000A-F
GTIN (EAN)	4044211109448
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.96 g
Weight per piece (including packaging)	1 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

Data sheet



4982.0 SI 6,3x32 2,000A-F

Technical data	
Dimensions	
Length	31.8 mm
Diameter of contact cap	6.35 mm
Dimensions	6,3x32 mm
Ratings	
Rated voltage	500 / 440 V
Rated current	2 A
Materials	
Contact caps	Brass
Surface	Nickel
Tube	Ceramic
Further technical data	
Trigger characteristic	Fast-acting (F)
Rated breaking capacity	50 kA @ AC 500 (cos? = 0,3)
Voltage drop	280 mV
Power loss (@ 1.5 ln)	1.6 W
Melting integral I2ts	2.5 A ² s
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet



4982.0 SI 6,3x32 2,000A-F

Media

Data sheet 4982.0 SI 6,3x32 2,000A-F



Accessories