

SWITCH HEAVY-DUTY TOGGLE DPDT

DPDT (Double-Pole, Double-Throw) function to switch 2 lines to 2 different positions.

It's good for most 1/2" Hole panel mount applications that are under 20 Amps at 125 Vac

FEATURES:

- Ratings: 20A @ 125 Vac, 10A @ 277 Vac, 1-1/2 H.P. (125 - 250)Vac
- For 0.500" Dia. Hole
- 15/32" - 32 THD Bushing, with Keyway
- Metal Bat Handle 0.650" tall
- 1 Hex Nut and 1 Knurl Nut
- Six # 6-32 Screw Terminals
- Operating Temperature: (0 to 65)°C
- Dielectric Strength: 1,500 Vac 1 minute
- Contact Resistance: 50 Milliohms max.
- Insulation Resistance: 100 Megohms (min.) 500 Vdc
- UL 94 Flammability Rating class 94V-1

Product Availability:

PART No.	DESCRIPTION	FUNCTION	
35-146	Toggle Switch DPDT	On - On	UPC: 010151541468
35-146-BU	Toggle Switch DPDT Bulk (10 pc)	On - On	UPC: 010151541451
35-148	Toggle Switch DPDT	On - Off - On	UPC: 010151541482
35-150	Toggle Switch DPDT	(On) - Off - (On)	UPC: 010151541529
35-151	Toggle Switch DPDT	On - Off - (On)	UPC: 010151541543

() = Momentary



PART No: **35-146**

HTS: 8536.50.9065
CoO: China

