



NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 4. DELRIN  
 5. Zinc Diecast

RoHS Compliant

Crimped Ferrule  
 Hex Crimp Size .255 (6.5)  
 Crimped Contact Pin  
 Hex Crimp Size .068 (1.7)

9	Ferrule	Note 1	Note 2	1
8	Contact Pin	Note 1	Note 3	1
7	Washer	Note 1	Note 2	1
6	Spring	SK5	Note 2	1
5	Retaining Ring	Note 1	Note 2	1
4	Gasket	Rubber	Red	1
3	Insulator	Note 4	Natural	1
2	Body	Note 1	Note 2	1
1	Shell	Note 5	Note 2	1

Dimensions are in Inches  
 Unless Otherwise Specified  
 Tolerances  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-13-2018
Checked	Date 12-13-2018
Drawn	Date 12-13-2018

<b>NTE Electronics</b>	
Title	BNC Crimp Plug (For RG-59, 62)
Drawing No.	06-B016
File No.	

No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	3/1	Issue	A
-----	-------------	----------	--------	------	-------------	-------	-----	-------	---