





1.4

1.3

11

1.2

Metric table

2

J

Dimensions	in:	millimeters	-	inches

d ₁	Length I ±0.2	25				d ₂ Thread	d ₃	h ₁	h ₂	r	t min.
8	55 *	64	88*	96	100	M 4	12	40	30	9	8
.31	2.17	2.52	3.46	<i>3.7</i> 8	<i>3.94</i>		.47	<i>1.57</i>	1.18	.35	.31
10	88*	100	120 *	180*	200	M 5	15	47	35	11	12
.39	3.46	3.94	4.72	7.09	7.87		.59	1.85	<i>1.38</i>	.43	.47
12 .47	125 4.92	160 6.30	200 7.87	250 9.84	-	M 6	-	60 2.36	44 1.73	12 .47	12 .47

* Suitable for 19" rack and enclosure layout

Specification	3
• Steel	
- Powder coated	
Black, RAL 9005, textured finish	• SW
- Chrome-plated finish	Ø CR
- Blackened finish	🖉 BT
Location disks	
Zinc die-cast, nickel-plated	
RoHS compliant	

On request

• Various metric size fasteners and kit packaging

• For certain minimum quantities, other lengths according to customer requirements

Information

GN 425.1 cabinet "U" handles are manufactured from a bent steel profile. Cabinet "U" handles with $\emptyset d_1 = 8$ and 10 mm are supplied with two location disks to guarantee a perfect location even with large holes in the cabinet. The location disks are enclosed in the package with the handle.

The manufacturing process allows the production of special lengths in relatively small quantities.

ŕ

The chrome-plated design is only conditionally suitable for outdoor use. The GN 425.1 stainless steel design should be given preference for constant outdoor use.

see also...

• Cabinet "U" Handles GN 425 (Steel, Not Offset)

How to order 1 Hand	lle diameter d ₁
1 2 3 2 Leng	th I
GN 425.1-10-100-CR 3 Mate	rial

2.4

2.2