	1	2		3	4	5	
Þ	000 015 Compliant		NOTOTION ROT			UL94-V0 IGE OPPER ALLOY ED EL M2.5 URE: -40 UP TO 115°C EE AND ROHS CULus 7A 300VAC SE: 1.6KV 20 mOhm max	Ē
G			PROJECTION:	GENERAL TOLERANCE			
F				$X = \frac{1}{2} 0.2$			-
D				.XX = <sup>+</sup> /_ 0.15			
С			APPROVAL: FBr	UNIT: MM	DESCRIPTION: SERIE 3597 - 5.08 MM IDC PLU FLANGES	G VERTICAL ENTRY WITH	
B A			4	SCALE: SHEET: 1/2			4
	09-JUN-15 PDF	AK		SHEET: 1/2	WERI PART NO: 691 359 740 0xx		

1	2	3	4	5	-
					_

А

В

С

## **Cautions and Warnings:**

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = <sup>+</sup> /_ 0.2			
E					.XX = <sup>+</sup> /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	Ъ
В					SCALE:			Р
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	<b>A4</b>	
REV	DATE	FILE	BY		DRAW: QL			