



## Main

Range of Product	Telemecanique Radio frequency identification XG
Accessory / separate part destination	XGSD XGSK XGCS
Product or Component Type	RS232/RS485 interface
Accessory / Separate Part Type	RS232C/RS485 line adaptor

## Complementary

Communication port converter	RS232C/RS485 no modem signals
Connection element	RS232/RS485 interface
Current Consumption	20 mA
[Ie] rated operational current DC	20 mA
Mounting Support	35 mm symmetrical DIN rail
Product mounting	35 mm symmetrical DIN rail
Net Weight	0.23 Lb(US) (0.105 kg) 0.22 lb(US) (0.1 kg)
[Us] rated supply voltage	18...30 V DC 24 V DC
Supply voltage limits	20...30 V
Transmission Rate	<= 19200 bit/s 19200 bauds
Electrical Connection	Screw connectors

## Ordering and shipping details

Category	22491-SENS,IDENTIFICATION DEVICE (XGK)
Discount Schedule	DS2
GTIN	3389110933611
Nbr. of units in pkg.	1
Package weight(Lbs)	3.84 oz (109.0 g)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.97 in (5 cm)
Package 1 width	2.56 in (6.5 cm)
Package 1 Length	5.12 in (13 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	28
Package 2 Weight	7.54 lb(US) (3.422 kg)
Package 2 Height	5.91 in (15 cm)

Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------