

APPLICABLE STANDARD				STORAGE TEMPERATURE RANGE		
RATING	OPERATING TEMPERATURE RANGE	-40°C T0 + 85°C (NOTE 1)	①	TEMPERATURE RANGE		
	OPERATING HUMIDITY RANGE	40% T0 + 80%		STORAGE HUMIDITY RANGE	-10°C T0 + 60°C (NOTE 2)	
	VOLTAGE	250V AC		VOLTAGE	30V AC	
CURRENT	AWG 22 T0 26 : 2A		UL • CSA RATING	CURRENT		
	AWG 28 : 1A			AWG 22 : 2A		
	AWG 30 : 0.5A			AWG 24 T0 28 : 1A		
				AWG 30 : 0.5A		
SPECIFICATIONS						
ITEM	TEST METHOD	REQUIREMENTS				
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.				
MARKING	CONFIRMED VISUALLY.					
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	100mA (DC OR 1000 Hz).	30mΩ MAX.		X	-	
INSULATION RESISTANCE	500V DC.	1000MΩ MIN.		X	-	
VOLTAGE PROOF	650V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.				
MECHANICAL CHARACTERISTICS						
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTATIONS.	① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-	
VIBRATION	FREQUENCY 10 TO 55 Hz. SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-	
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.					
ENVIRONMENTAL CHARACTERISTICS						
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→-5 TO 35→+85 →-5 TO 35 °C TIME 30→5 TO 15 →30 →5 TO15 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 1000MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-	
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 500MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
△ 1	DIS-H-008540	MI. SAKIMURA	HK. UMEHARA	14. 02. 26		
		APPROVED	TS. SAKATA	09. 06. 03		
		CHECKED	TS. FUKUSHIMA	09. 06. 03		
		DESIGNED	TH. YOSHIZAWA	09. 05. 30		
		DRAWN	YK. NAKATSU	09. 05. 27		
Note Q1:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-314124-01		
HRS		SPECIFICATION SHEET		PART NO.		
		HIROSE ELECTRIC CO., LTD.		CODE NO.		
				DF11GZ-*DS-2V (22)		
		CL543		△ 1/2		

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
RESISTANCE TO SOLDERING HEAT	1) AUTOMATIC SOLDERING (REFLOW) 《REFLOW AREA》 MAX 250°C WITHIN 10 sec. MIN 230°C WITHIN 60 sec. 《PREHEATING AREA》 150 TO 180°C 90 TO 120 sec. PUT THROUGH IN REFLOW FUMACE TWICE. FEAVE IN AMBIENT TEMPERATURE AND HUMIDITY FOR 1 HOUR. CONNECTOR TEMPERATURE TO BE AMBIENT FOR SECOND REFLOW. 2) MANUAL SOLDERING SOLDERING IRON TEMPERATURE :290±10°C, SOLDERING TIME :3s. NO STRENGTH ON CONTACT.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	-
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 230±5°C FOR IN IMMERSION , DURATION, 3 s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMERSIED.	X	-

--	--	--	--	--

REMARKS

NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT.
 NOTE 2:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD , AFTER PCB BOARD , OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERM STORAGE DURING TRANSPORTATION.
 NOTE 3:THE TEMPERATURE PROFILE SHALL BE APPLIED WITHIN 168 HOURS AFTER OPENING MOISTURE-PROOF PACKAGING. WHEN 168 HOURS PASSED AFTER OPENING , APPLY THE BOTTOM REQUIREMENTS.
 《REFLOW AREA》
 MAX 240°C WITHIN 10 sec.
 MIN 230°C WITHIN 60 sec.
 《PREHEATING AREA》
 150 TO 180°C 90 TO 120 s.

Unless otherwise specifid , refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. ELG4-314124-01

HRS	SPECIFICATION SHEET	PART NO.	DF110Z-*DS-2V (22)	
	HIROSE ELECTRIC CO., LTD.	CODE NO	CL543	2/2