



CONNECTOR SPECIFICATION:

VOLTAGE RATING	600V AC/DC
AMPERAGE RATING	2P: 18 AMPS, 3P: 18 AMPS, 4P: 15 AMPS
PROTECTION	IP67
OPERATING TEMP.	-20°C TO 105°C
UL CERTIFICATIONS	UL RECOGNIZED, FILE NO. E46237

POLES	MATERIAL NO.	ENGINEERING NO.	FINISHED LENGTH
4	1300000074	32638	6.0 FT. +2.19"-0 [183CM+56mm-0]
4	1300000076	32639	12.0 FT. +3.50"-0 [366 CM +89mm-0]

ITEM	COMPONENT	MATERIAL	FINISH
5	LABEL	VINYL	YELLOW
4	COUPLING	THERMOPLASTIC	BLACK
3	CONTACT SOCKET	COPPER ALLOY	UN-PLATED
2	OVERMOLD	RUBBER	YELLOW
1	CABLE-14 AWG SOW	CPE JACKET	YELLOW

RELEASED EC NO: IPG2013-0663 DRWN: RSTONE 2012/11/20 CHKD: K JOZWIK APPR: JFMURPHY 2013/02/07	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH/MM		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
		4 PLACES ±--- ±---	3 PLACES ±--- ±---	DRAWN BY RSTONE	DATE 2012/11/20	TITLE QUICK CHANGE CABLE ASSY 2-4P FEMALE, 14 AWG		
		2 PLACES ±--- ±.01	1 PLACE ±0.3 ±---	CHECKED BY K JOZWIK	DATE 2012/11/28			
		ANGULAR ±2°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY JFMURPHY	DATE 2013/02/07	
A	REV	SEE CHART		MATERIAL NO.	DOCUMENT NO. SD-130000-004	SHEET NO. 1 OF 1		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION