



Notes:

Electrical:

1. Voltage Rating: 125VAC
2. Current Rating: 1.5AMP
3. Contact Resistance: 45mΩ max.
4. Insulation Resistance: 1000MΩ min. @ 500VDC
5. Dielectric Strength: 1000VAC RMS 60Hz, 1 min.
6. Operating: 750 cycles min.

Mechanical:

1. Housing Material: PBT UL94V-0 Black
2. Contact Material: Phosphor Bronze l=0.35mm
3. Contact Plating: 50u" Gold on contact area
100-200u" Tin on solder area
All over 30-50u" Nickel
4. PCB Retention Pre-solder: 1 LB min.
5. PCB Retention Post-solder: 10 LBS min.

Environmental:

1. Storage: -40°C to +85°C
2. Operation: -40°C to +85°C

Mates with Modular Plug conforming to TIA-1096-A

Package: Tray

RoHS compliant
Unit: mm



File No.: E3345352

Scale	Free		
TOLERANCE			
.X	±0.20	Drawn	Date
.XX	±0.15	Approved	02.03.2016
.XXX	±0.10		
DIM		TOL	
Angle	±5°		
		① Add UL No.	
		① Drawn	
		Date	
		Name	
		Modification	
		Id.	

ASSMANN
WSW components

Customer-No.
ASSMANN WSW-No. AMUJH-6-T-R-P10
Drawing-No.
ASS 7105 CO
Replace
rev01
Sheet