



Material And Finish

Shell: Steel, Nickel plated

Insulator: PBT with glass-fiber reinforcement, UL 94V-0, color-black

Contact Material:
Plug - Brass

Contact Plating Options:
Standard Option:
Gold flash on mating end,
Tin on termination end,
with entire contact Nickel

-15 Option:
0,000015" Gold on mating end,
Tin on termination end,
with entire contact Nickel

-30 Option:
0,000030" Gold on mating end,
Tin on termination end,
with entire contact Nickel

Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Dielectric Withstanding Voltage:
500 V (rms) AC for 1 minute

Insulation Resistance:
more than 1000 Megohm
at 500 V DC

Contact Resistance:
13 milliohm Max

Temperature Rating:
-55°C to +105°C

Ordering Information

Part Number	Contact Area Plating Finish
K88X-BD-25P-BR	Gold Flash (standard option)
K88X-BD-25P-BR15	15u" Gold (15 option)
K88X-BD-25P-BR30	30u" Gold (30 option)

RoHS COMPLIANT



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	03/15/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	03/15/06
A2	1/24/08	ECO# 07-052	WILL H.	H. MA		
A3	12/31/17	ECO #17-035	G. Serrato	C. Furumasu		

K88X-BD-25P-BR

Vertical 25 pos. Male D-Sub, RoHS Compliant

Precision Formed Contacts, w/ Boardlocks

