


Data sheet | Item number: 285-168

Fixing element; for 95 mm² high-current terminal blocks; orange

www.wago.com/285-168



Data

Material Data

Note (material data)

Information on material specifications can be found here

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Color	orange
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Weight	1.6 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	50 (25) pcs
Packaging type	box
Country of origin	PL
GTIN	4055143578172
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

285-168 X81 - Datei	2019 年7月1日	xml 2.8 kB	Download
285-168 docx - Datei	2019 年7月1日	docx 13.8 kB	Download
285-168 doc - Datei	2019 年7月1日	doc 22.5 kB	Download

Subject to changes. Please also observe the further product documentation!



Additional Information

pdf
2.2 MB Download

CAD/CAE-Data

CAE data

EPLAN Data Portal 285-168 URL Download

CAD data

2D/3D Models 285-168 URL Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 285-168 URL Download
Fixing element; for 95 mm² high-current terminal blocks; orange

Installation Notes

Installation



Optionally, insert block-to-block connector (285-168) into housing slot.



Align and snap high-current, through terminal blocks together.

Subject to changes. Please also observe the further product documentation!