# 1-1586038-2 ACTIVE

#### VAL-U-LOK

TE Internal #: 1-1586038-2

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 12 Position, 4.2 mm [.165 in] Centerline, Printed Circuit Board, UL 94V-0

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Header

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 12

Centerline (Pitch): 4.2 mm [ .165 in ]

### **Features**

### Product Type Features

Operating Voltage

**Contact Features** 

Contact Layout

Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	12
PCB Mount Orientation	Vertical
Number of Power Positions	12
Number of Rows	2
Electrical Characteristics	

600 VAC

Inline, Matrix



Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	9 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	2.03 μm[80 μin]
Termination Features	
Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	Natural
Housing Color Housing Material	Natural Nylon
Housing Material	
Housing Material  Dimensions	Nylon
Housing Material  Dimensions  Compatible Insulation Diameter (Max)	Nylon  2.39 mm[2.39 in]
Housing Material  Dimensions  Compatible Insulation Diameter (Max)  Connector Height	Nylon  2.39 mm[2.39 in]  12.8 mm[.504 in]
Housing Material  Dimensions  Compatible Insulation Diameter (Max)  Connector Height  PCB Thickness (Recommended)	Nylon  2.39 mm[2.39 in]  12.8 mm[.504 in]  .06 mm[1.6 in]
Housing Material  Dimensions  Compatible Insulation Diameter (Max)  Connector Height  PCB Thickness (Recommended)  Product Width	Nylon  2.39 mm[2.39 in]  12.8 mm[.504 in]  .06 mm[1.6 in]  9.75 mm[.384 in]
Housing Material  Dimensions  Compatible Insulation Diameter (Max)  Connector Height  PCB Thickness (Recommended)  Product Width  Product Length	Nylon  2.39 mm[2.39 in]  12.8 mm[.504 in]  .06 mm[1.6 in]  9.75 mm[.384 in]  26.4 mm[1.039 in]
Housing Material  Dimensions  Compatible Insulation Diameter (Max)  Connector Height  PCB Thickness (Recommended)  Product Width  Product Length  Compatible Insulation Diameter Range	Nylon  2.39 mm[2.39 in]  12.8 mm[.504 in]  .06 mm[1.6 in]  9.75 mm[.384 in]  26.4 mm[1.039 in]  1.2 – 3.1 mm[.047 – .122 in]
Housing Material  Dimensions  Compatible Insulation Diameter (Max)  Connector Height  PCB Thickness (Recommended)  Product Width  Product Length  Compatible Insulation Diameter Range  Row-to-Row Spacing	Nylon  2.39 mm[2.39 in]  12.8 mm[.504 in]  .06 mm[1.6 in]  9.75 mm[.384 in]  26.4 mm[1.039 in]  1.2 – 3.1 mm[.047 – .122 in]



Circuit Application	Power
Identification Marking	
Circuit Identification Feature	With
Industry Standards	
UL Rating	Recognized
Agency/Standard	UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	225
Packaging Method	Box & Tray, Tray

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach




# Compatible Parts









# Customers Also Bought


















### **Documents**

Product Drawings
12P VRT HDR VAL-U-LOK V0

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1586038-2\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1586038-2\_C.3d\_igs.zip

English

**Customer View Model** 



### ENG\_CVM\_CVM\_1-1586038-2\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

# Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_AND\_SOCKET\_CONNECTORS\_CATALOG

English

**Product Specifications** 

**Product Specification** 

English

Product Environmental Compliance

**Product Compliance Document** 

English

**Product Compliance Document** 

English

**Agency Approvals** 

**UL Report** 

English