


Recommended
Cable Stripping Dim's

Crimped Ferrule
Hex Crimp Size .213 (5.41)
Contact Pin to Solder

RoHS Compliant

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 4. Teflon
 5. Passivated



8	Ferrule	Copper	Note 2	1	
7	Cover	Note 1	Note 2	1	
6	Gasket	Silicone	Red	1	
5	Retainer Ring	SUS 304	Note 5	1	
4	Contact Pin	Note 1	Note 3	1	
3	Insulator	Note 4	Natural	1	
2	Housing with Barrel	Note 1	Note 2	1	
1	Shell	Note 1	Note 2	1	
No	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches
Unless Otherwise Specified
Tolerances
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

Part No.	
Approved	Date 5-5-2015
Checked	Date 5-5-2015
Drawn	Date 5-5-2015

NTE Electronics	
Title SMA R/ACrimp Plug (For RG-58, 58A, 58C, 141)	
Drawing No. 06-S009	
File No.	

A

A

F

F

E

E

D

D

C

C

B

B

1

2

3

4

5

6

7

8

1

2

3

4

5

6

7

8