



NOTES:

1. RECOMMENDED DIAMETER FOR THROUGH HOLE (SCREW/NUT COMBINATION) HARDWARE MOUNTING METHOD. OTHER METHODS WILL REQUIRE HOLES WITH DIFFERENT DIMENSIONS AND PARAMETERS.
2. HOUSING TOLERANCE +/- .25 UDS.

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY, CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER.

REV	CHANGE DESCRIPTION	DATE	BY
3	Added enhanced holding tabs.	4-16-21	DDF
2	1) ADDED NOTE 2.	8-6-12	BEM
1	INITIAL RELEASE	6-5-12	BEM

DIMENSIONS: MM		TITLE	
DRAFT BY: BEM DATE: 6-5-12		SHEET F - SCREW MOUNT SOLDER TAB CONTACTS	
DRAFTING APPROVAL: SRK DATE: 6-5-12		ASSY NUMBER: 83030610	
MATERIAL:		DO NOT SCALE	INTERPOWER CORPORATION
		SHEET 1 OF 1	