CSICD10-1200

SURFACE MOUNT SILICON CARBIDE SCHOTTKY RECTIFIER 10 AMP, 1200 VOLT



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CSICD10-1200 is a silicon carbide Schottky rectifier designed for high frequency systems where energy efficiency and thermal performance are critical design elements.

MARKING CODE: SICD1200



APPLICATIONS:

- Power inverters
- Motor drives
- Switch-mode power supplies
- Power factor correction

FEATURES:

- Low profile package
- Low switching loss
- Stable switching over temperature extremes

MAXIMUM RATINGS: (T_C=25°C unless otherwise noted)

	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	1200	V
Peak Reverse Surge Voltage	V_{RSM}	1200	V
DC Blocking Voltage	v_R	1200	V
Average Rectified Forward Current (T _C =157°C)	IO	10	Α
Continuous Forward Current (T _C =157°C)	Ι _F	10	Α
Peak Forward Surge Current, tp=10ms	I _{FSM}	120	Α
Single Pulse Avalanche Energy (Note 1)	E _{AS}	88	mJ
Power Dissipation	P_{D}	150	W
Power Dissipation (T _C =157°C)	P_{D}	42	W
Operating and Storage Junction Temperature	T _J , T _{stg}	-55 to +175	°C
Thermal Resistance	ΘJC	1.6	°C/W

Note 1: L=10mH, I_{PK} =4.1A, V_{DD} =100V, Initial T_J =25°C

ELECTRICAL CHARACTERISTICS: (T _J =25°C unless otherwise noted)				
SYMBOL	TEST CONDITIONS	TYP	MAX	UNIT
I_{R}	V _R =1200V	100	640	μΑ
I_{R}	V _R =1200V, T _J =175°C	1.0		mA
V_{F}	I _F =10A	1.4	1.6	V
V_{F}	I _F =10A, T _J =150°C	1.85	2.3	V
VF	I _F =10A, T _J =175°C	2.0	2.6	V
$Q_{\mathbb{C}}$	V _R =800V	51		nC
CJ	V_R =1.0V, f=1.0MHz	510		pF
CJ	V _R =400V, f=1.0MHz	48		pF
CJ	V _R =800V, f=1.0MHz	41		pF


R3 (13-October 2017)


CSICD10-1200

SURFACE MOUNT SILICON CARBIDE SCHOTTKY RECTIFIER 10 AMP, 1200 VOLT



DPAK-2L CASE - MECHANICAL OUTLINE






DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
Α	0.080	0.100	2.03	2.54
В	0.018	0.035	0.46	0.89
С	0.035	0.050	0.89	1.27
D	0.230		5.84	
E	0.021	0.027	0.53	0.69
F	0.015	0.025	0.38	0.64
G	0.051	0.071	1.30	1.80
Н	0.250	0.270	6.35	6.86
J	0.195	0.215	4.95	5.46
K	0.230	0.250	5.84	6.35
Ĺ	0.087	0.118	2.21	3.00
М	0.025	0.045	0.64	1.14
N	0.1	80	4.	57
DPAK_2L (REV: R1)				

DPAK-2L (REV: R1)

PIN CONFIGURATION



LEAD CODE:

- 1) Cathode
- 2) Anode

Tab) Cathode

MARKING CODE: SICD1200


R3 (13-October 2017)


CSICD10-1200


SURFACE MOUNT SILICON CARBIDE SCHOTTKY RECTIFIER 10 AMP, 1200 VOLT




TYPICAL ELECTRICAL CHARACTERISTICS









OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- · Package details
- Application notes
- · Application and design sample kits
- · Custom product and package development

REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (001)



Product End of Life Notification

PDN ID:	PDN01142
Notification Date:	2/04/20
Last Buy Date:	8/04/20
Last Shipment Date	2/04/21

Summary: All silicon carbide Schottky rectifiers in the DPAK-2L and TO-220-2 packages are discontinued and now classified as End of Life (EOL). However, Central will continue to support these products in bare die form.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

Central Part Number	Replacement
CSICD05-1200 BK	N/A, Stock Only
CSICD05-1200 TR13	N/A, Stock Only
CSICD10-1200 BK	N/A, Stock Only
CSICD10-1200 TR13	N/A, Stock Only
CSICD10-650 BK	N/A, Stock Only
CSICD10-650 TR13	N/A, Stock Only
CSIC10-1200	N/A, Stock Only
CSIC10-1200 SL	N/A, Stock Only
CSIC10-650 SL	N/A, Stock Only

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002