



Glove Laundering

For proper operation, the ESD Gloves must be laundered periodically. Woolite works well. Liquid detergents are better than dry detergents in that there is less caking and frictional wear. Launder glove in cool or warm water, tumble dry with low heat or hang dry. Machine washing works well if using a standard home machine on gentle cycle. It is not recommended to launder these gloves in heavy industrial laundry machines as it will lead to premature wear. Gloves should be tumbled dry using low heat. DO NOT BLEACH. After laundering, verify Rtt 1 x 10⁵ < 1 x 10⁹ ohms. Desco's ESD inspection gloves will retain their ESD properties for 25 washing or approximately 1 year.

*Not recommended for use above 104°F (40°C)

- A. Dissipative (1 x 10⁵ to < 1 x 10⁸ ohms) Thunderon[®] Fibers
 Protective Carrier Yarn
 Seamless Fine Gauge Knit
- B. Polyurethane Coated Palm and Fingers
- C. Non-Scratch Touchscreen Compatible

| Item | Size | Cuff Color | |
|---------------|----------|------------|--|
| <u>68124</u> | X-Small | Orange | |
| <u>68125</u> | Small | Light Grey | |
| <u>68126</u> | Medium | Green | |
| <u>68127</u> | Large | Brown | |
| <u>68128</u> | X-Large | Yellow | |
| <u>68129</u> | XX-Large | Dark Grey | |
| Sold in pairs | | | |

| Protection from mechanical risks. Tested per EU EN388. | | |
|--|-------------------|--|
| Test | Performance Level | |
| 6.1 Abrasion Resistance | 4 | |
| 6.2 Blade Cut Resistance | 1 | |
| 6.3 Tear Resistance | 3 | |
| 6.4 Puncture Resistance | 1 | |
| | | |

Specifications and procedures subject to change without notice DISSIPATIVE NYLON GLOVES WITH POLYURETHANE COATING

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 68124 DATE: March 2019