



Shellsize	A	B	C	D	E	F <sup>+1</sup> <sub>-3</sub>	G	Cable $\phi$	Part-NO.
1	40.76	25.00	SW 20	51.0	22.0	77.0	44.0	5 - 10	165X15319X
2	49.06	33.30	SW 24	51.0	22.0	79.0	52.0	7 - 12	165X15329X
3	62.80	47.04	SW 24	59.5	22.0	87.5	52.0	7 - 12	165X15339X
4	78.86	63.50	SW 30	67.0	22.0	99.0	52.0	9 - 16	165X15349X
5	76.46	61.10	SW 40	67.0	24.8	107.0	52.0	13 - 20	165X15359X

Directive 2002/95 EC  
„RoHS“  
Compliant

- NOTES:**  
 1. HOOD: ABS V0, METALLIZED  
 2. SCREWS: STAINLESS STEEL

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

---

NAME: TITLE:

---

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

**DO NOT ALTER CAD DRAWING BY HAND**

2 x b	Ä 3353	29.04.2009	Lehmen
a	Origin		
rev.	description	date	name

tolerance	dim. in mm	scale:	1:1
		material:	SEE NOTES
2004	date	name	title: <b>WATER RESISTANT D-SUB HOOD</b> 9-50pos. with jack screw
drawn	15.08.	Lehmenkühler	
appd.	15.08.	Kühle	
	norm		dwg no: AutoCAD 2004 DIN-A 3 sh: 1/1
	d-old		
CONEC®		part no:	SEE TABLE