

3M™ EAD-861

Technical Data Sheet

April 2020

3M™ EAD-861 is classified as an IATD R3 product. This product does not have a typical 3M IATD adhesive tape product number and it will not be found in the catalog or via online search. It is only available on a limited basis. Please consult your 3M account rep for further information.

Product Description **Note:** The data presented in this data sheet are best estimates for the current product construction. User should not make any business plans in reliance upon the future availability or the current properties of this product.

3M™ EAD-861 features 3M™ Adhesive 300MP which is ideal for bonding a wide variety of similar and dissimilar materials such as metals, glass, wood, papers, paints and many plastics.

Construction Information

<u>Release Liner</u> <u>Type,Print</u>	<u>Backside</u> <u>Adhesive</u> <u>Type/Thicknes</u>	<u>Carrier</u>	<u>Faceside</u> <u>Adhesive</u> <u>Type/Thicknes</u>
83# PCK liner No Print	300MP 0.002 (0.051mm)	Clear PET 0.0005 (0.0127mm)	300MP 0.005 (0.127mm)

For Additional Information

To request additional product information or to arrange for sales assistance, call 3M Technical Service at 651 733-4872. Address correspondence to 3M Industrial Adhesives and Tapes Division, 3M Center, Building 230 -2G-14, St. Paul, MN 55144-1000. Our fax number is 651-736-3514

3M

EAD-861

Important Notice The statements and technical information contained herein are based on tests and data which 3M believes to be reliable, but the accuracy or completeness of such statements and technical information is not guaranteed. User is responsible for determining whether a specific 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

No Warranty 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limitation of Remedies And Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



Industrial Adhesives and Tapes Division

3M Center, Building 220-5E-06
St. Paul, MN 55144-1000
www.3M.com/adhesives

Printed in U.S.A.
©3M 2003