
# PT Platform Scales






PT industrial scales offer durability and quality construction for a variety of different applications. The PT features a large, steel base with a diamond plate surface, adjustable leveling feet and cable. Optional ramps facilitate loading and unloading heavy objects. The platforms are available with or without indicators. Adam offers a range of indicators including the GK, GC, AE 403, AE 503 and AE 504.

Quality construction with a diamond-plate surface for ultimate durability and performance







#### **Features**

- · Rugged construction stands up to industrial use
- · Diamond-plate surface for added grip
- · Optional ramps facilitate loading and unloading
- Can be used with any Adam indicators
- Approximately five-meter/15-foot shielded cable

## **Applications**

- Weighing
- Parts counting
- Checkweighing
- Dynamic / animal weighing

### **Compatible Indicators**



**AE 403 Indicator** 



**GK Indicator** 



**GC** Indicator



**AE 503 Indicator** 



**AE 504 Indicator** 

#### **About ADAM:**

For the past 50 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.





#### **Product Details**

| Model                    | PT 110                             | PT 310-5        | PT 310-10           | PT 112                    | PT 312-5           | PT 312-10           | PT 115                             | PT 315-5        | PT 315-10                             | PT 112M                   | PT 312-5M       |
|--------------------------|------------------------------------|-----------------|---------------------|---------------------------|--------------------|---------------------|------------------------------------|-----------------|---------------------------------------|---------------------------|-----------------|
| Capacity                 | 2500lb / 1000kg                    | 5000lb / 3000kg | 10000lb /<br>4500kg | 2500lb / 1000kg           | 5000lb / 3000kg    | 10000lb /<br>4500kg | 2500lb / 1000kg                    | 5000lb / 3000kg | 10000lb /<br>4500kg                   | 2500lb / 1000kg           | 5000lb / 3000kg |
| Readability              | 0.5lb / 0.2kg                      | 1lb / 0.5kg     | 2lb / 1kg           | 0.5lb / 0.2kg             | 1lb / 0.5kg        | 2lb / 1kg           | 0.5lb / 0.2kg                      | 1lb / 0.5kg     | 2lb / 1kg                             | 0.5lb / 0.2kg             | 1lb / 0.5kg     |
| Excitation Voltage       | 5 - 10 VAC / DC                    |                 |                     |                           |                    |                     |                                    |                 |                                       |                           |                 |
| Loadcells                | 4                                  |                 |                     |                           |                    |                     |                                    |                 |                                       |                           |                 |
| Pan Size                 | 39.4"x39.4" / 1000x1000mm          |                 |                     | 47.2"x47.2" / 1200x1200mm |                    |                     | 59.1"x59.1" / 1500x1500mm          |                 |                                       | 47.2"x47.2" / 1200x1200mm |                 |
| Operating<br>Temperature | -10° to 40°C / 14° to 104°F        |                 |                     |                           |                    |                     |                                    |                 |                                       |                           |                 |
| Housing                  | Mild steel base                    |                 |                     |                           |                    |                     |                                    |                 |                                       |                           |                 |
| Cable Length             | 10°/3M                             |                 |                     |                           |                    |                     |                                    |                 |                                       |                           |                 |
| Overall Dim. (WxDxH)     | 39.4"x39.4"x4.3" / 1000x1000x110mm |                 | 00x110mm            | 47.2"x47.2                | 2"x4.3" / 1200x120 | 0x110mm             | 59.1"x59.1"x4.3" / 1500x1500x110mm |                 | 47.2"x47.2"x4.3" /<br>1200x1200x110mm |                           |                 |
| Net Weight               |                                    | 136.6lb / 62kg  |                     |                           | 174.1lb / 79kg     |                     |                                    | 244.6lb / 111kg |                                       | 174.1lb                   | / 79kg          |
| Approvals                | N/A                                |                 |                     |                           |                    |                     |                                    |                 |                                       | NTEP / Measurement Canada |                 |

#### **Accessories**

# Item Number Description 700100199 Mild Steel Ramp - PT 10R (1000mm wide) 700100200 Mild Steel Ramp - PT 12R (1200mm wide) 700100201 Mild Steel Ramp - PT 15R (1500mm wide)

# **Key Accessories**



#### Mild Steel Ramp

Compatible with several Adam indicators, the PT is designed to weigh pallets, crates and large containers. PT contains an innovative X frame beneath the platform, which reinforces and strengthens the platform for improved support.

Supplied by

Adam Equipment follows a policy of continuous improvement and reserves the right to change specification and pricing without notice. Adam Equipment's standard terms and conditions of sale apply. Errors and omissions excepted.