

5.0V 1.5F ULTRACAPACITOR MODULE

BMOD0001 P005 B02
EMHSR-0001C5-005R0

FEATURES AND BENEFITS

- High performance product with low ESR
- Exceptional shock and vibration resistance
- Long lifetimes with up to 500,000 duty cycles*
- Compliant with RoHS and REACH requirements

TYPICAL APPLICATIONS

- Automotive
- UPS System
- Actuators
- Emergency Lighting
- Telematics
- Security Equipment
- Backup System
- Smoke Detectors
- Advanced Metering



PRODUCT SPECIFICATIONS

ELECTRICAL

Rated Voltage, V_R	5.0 VDC
Surge Voltage ¹	5.4 VDC
Rated Capacitance, C^3	1.5 F
Min. / Max. Capacitance, Initial	1.35 F / 1.8 F
Typical Capacitance, Initial ^{2,3}	1.55 F
Rated (Max.) ESR _{DC} , Initial ³	130 mΩ
Typical ESR _{DC} , Initial ^{2,3}	109 mΩ
Maximum Leakage Current ⁴	5 μA
Maximum Peak Current, Non-repetitive ⁵	3.1 A

PHYSICAL

Nominal Mass	3.4 g
--------------	-------

POWER & ENERGY

Operating Temp. Range	Standard (-40°C to 65°C) at 5.0V	Extended (-40°C to 85°C) at 4.6V
Maximum Stored Energy, $E_{max}^{6,9}$	5.2 mWh	4.4 mWh
Gravimetric Specific Energy ⁶	1.5 Wh/kg	1.3 Wh/kg
Usable Specific Power ⁶	6.7 kW/kg	5.7 kW/kg
Impedance Match Specific Power ⁶	14.1 kW/kg	11.9 kW/kg

SAFETY

Certifications	RoHS, REACH
----------------	-------------

TYPICAL CHARACTERISTICS

THERMAL

Typical Thermal Resistance (R_{th} , Housing) ⁸	77°C/W
Typical Thermal Capacitance (C_{th})	2.8 J/°C
Usable Continuous Current (BOL) ($\Delta T = 15\text{ °C}$) ^{8,10}	1.2 A
Usable Continuous Current (BOL) ($\Delta T = 40\text{ °C}$) ^{8,10}	2.0 A


LIFE*

Projected DC Life at Room Temperature (At rated voltage and 25°C, EOL ¹⁰)	10 years
DC Life at High Temperature (At rated voltage and 65°C, EOL ¹⁰)	1,500 hours
DC Life at De-rated Voltage & Higher Temperature (At 4.6V and 85°C, EOL ¹⁰)	1,500 hours
Projected Cycle Life at Room Temperature ⁷ (Constant current charge-discharge from V_R to $1/2V_R$ at 25°C, EOL ¹⁰)	500,000 cycles
Shelf Life (Stored uncharged at 25°C, ≤ 50% RH)	4 years

*Results may vary. Additional terms and conditions, including the limited warranty, apply at the time of purchase. See the warranty details for applicable operating and use requirements.

Datasheet: 5.0V 1.5F ULTRACAPACITOR MODULE

- Surge Voltage**
Absolute maximum voltage, non-repetitive. Duration not to exceed 1 second.
- "Typical" values represent mean values of production sample.
- Rated Capacitance & ESR_{DC} (measure method)**
 - Capacitance: Constant current charge ($4 * C * V_R$ [mA]) to V_R , 5 min hold at V_R , constant current discharge ($4 * C * V_R$ [mA]) to 0.1 V.
e.g. in case of 5.0V 1.5F module, $4 * 1.5 * 5.0 = 30$ mA.
 - ESR_{DC}: Constant current charge ($40 * C * V_R$ [mA]) to V_R , 5 min hold at V_R , constant current discharge ($40 * C * V_R$ [mA]) to 0.1 V.
e.g. in case of 5.0V 1.5F module, charge with $4 * 1.5 * 5.0 = 30$ mA and discharge with $40 * 1.5 * 5.0 = 300$ mA.



where C is the capacitance (F);
I is the absolute value of the discharge current (A);
 V_R is the rated voltage (V);
 V_1 is the measurement start voltage, $0.8 * V_R$ (V);
 V_2 is the measurement end voltage, $0.4 * V_R$ (V);
 t_1 is the time from start of discharge to reach V_1 (s);
 t_2 is the time from start of discharge to reach V_2 (s);
ESR_{DC} is the DC-ESR (Ω);
 ΔV is the voltage drop during first 10ms of discharge (V).

- Maximum Leakage Current**
 - Current measured after 72 hrs at rated voltage and 25°C. Initial leakage current can be higher.
 - If applicable, module leakage current is the sum of cell and balancing circuit leakage currents.
- Maximum Peak Current**
 - Current needed to discharge cell/module from rated voltage to half-rated voltage in 1 second.


$$I = \frac{\frac{1}{2} V_R}{\Delta t / C + ESR_{DC}}$$

where Δt is the discharge time (sec); $\Delta t = 1$ sec in this case

- The stated maximum peak current should not be used in normal operation and is only provided as a reference value.
- Energy & Power (Based on IEC 62391-2)**
 - Maximum Stored Energy, E_{max} (Wh) = $\frac{\frac{1}{2} C V_R^2}{3,600}$
 - Gravimetric Specific Energy (Wh/kg) = $\frac{E_{max}}{mass}$
 - Usable Specific Power (W/kg) = $\frac{0.12 V_R^2}{ESR_{DC} \times mass}$
 - Impedance Match Specific Power (W/kg) = $\frac{0.25 V_R^2}{ESR_{DC} \times mass}$
 - Cycle Life Test Profile**
Cycle life varies depending upon application-specific characteristics. Actual results will vary.
 - Temperature Rise at Constant Current**
 - $\Delta T = I_{RMS}^2 \times ESR_{DC} \times R_{th}$

where ΔT : Temperature rise over ambient (°C)
 I_{RMS} : Maximum continuous or RMS current (A)
 R_{th} : Thermal resistance, module to ambient (°C/W)
ESR_{DC}: Rated (Max.) ESR_{DC} (Ω).
(Note: Design should consider EOL ESR_{DC} for application temperature rise evaluation.)
 - Per United Nations material classification UN3499, all Maxwell ultracapacitors have less than 10 Wh capacity to meet the requirements of Special Provisions 361. Both individual ultracapacitors and modules composed of those ultracapacitors shipped by Maxwell can be transported without being treated as dangerous goods (hazardous materials) under transportation regulations.
 - BOL: Beginning of Life, rated initial product performance**
EOL: End of Life criteria.
 - Capacitance: 80% of min. BOL rating
 - ESR_{DC}: 2x max. BOL rating

BMOD0001 P005 B02



Part Description	Dimensions (mm)						
	W (max.)	L (max.)	D (max.)	d (± 0.05)	H1 (min.)	H2 (min.)	A (± 0.1)
BMOD0001 P005 B02	17.5	23.0	9.5	0.60	15.0	19.0	8.6

When ordering, please reference the Maxwell Model Number below.

Maxwell Model Number: BMOD0001 P005 B02
Maxwell Part Number: 133730
Previous Model Number: EMHSR-0001C5-005R0

Products and related processes may be covered by one or more U.S. or international patents and pending applications. Please see www.maxwell.com/patents for more information. Product dimensions are for reference only unless otherwise identified. Maxwell Technologies reserves the right to make changes without further notice to any products herein. "Typical" parameters which may be provided in Maxwell Technologies datasheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Please contact Maxwell Technologies directly for any technical specifications critical to application.

Maxwell Technologies, Inc.
Global Headquarters
 3888 Calle Fortunada
 San Diego, CA 92123
 USA
 Tel: +1 (858) 503-3300
 Fax: +1 (858) 503-3301

Maxwell Technologies, GmbH
 Leopoldstrasse 244
 80807 Munich
 Germany
 Tel: +49 (0)89 4161403 0
 Fax: +49 (0)89 4161403 99

Maxwell Technologies Shanghai Trading Co., Ltd.
 Room 1005, 1006, and 1007
 No. 1898, Gonghexin Road,
 Jin An District, Shanghai 2000072,
 P.R. China
 Tel: +86 21 3852 4000
 Fax: +86 21 3852 4099

Maxwell Technologies Korea Co., Ltd.
 17, Dongtangiheung-ro
 681 Beon-gil, Giheung-gu,
 Yongin-si, Gyeonggi-do 17102
 Republic of Korea
 Tel: +82 31 289 0721
 Fax: +82 31 286 6767

MAXWELL TECHNOLOGIES, MAXWELL, MAXWELL CERTIFIED INTEGRATOR, ENABLING ENERGY'S FUTURE, DURABLU, NESSCAP, XP, BOOSTCAP, D CELL and their respective designs and/or logos are either trademarks or registered trademarks of Maxwell Technologies, Inc., and/or its affiliates, and may not be copied, imitated or used, in whole or in part, without the prior written permission Maxwell Technologies, Inc. All contents copyright © 2020 Maxwell Technologies, Inc. All rights reserved. No portion of these materials may be reproduced in any form, or by any means, without prior written permission from Maxwell Technologies, Inc.

