

**Ratings**

Temperature: -40 ~ 70 °C  
Voltage: 150 V

**Conductor**

Gauge: 28 AWG, 0.081 mm<sup>2</sup>  
Material: tinned copper strands  
Stranding:  $\phi$  0.05 x 40  
Resistance at 20 °C: 240  $\Omega$ /km max

**Insulator**

Material: HDPE  
Color: black, white  
Outer diameter:  $\phi$  0.7  $\pm$  0.10 mm  
Nominal thickness: 0.15 mm  
Resistance at 20 °C: 1000 M $\Omega$ /km min

**Shield**

Type: spiral  
Material: tinned copper strands  
Strand size:  $\phi$  0.08 mm  
Coverage: 90 % minimum

**Outer jacket**


Material: TPU, 70 °C  
Color: black  
Nominal thickness: 0.50 mm  
Diameter:  $\phi$  2.6  $\pm$  0.15 mm

**Filler**

Material: aramid fiber

**Tests**

Tensile strength: 35.7 kgf  
Dielectric test: 1500 V dc for 1 minute without breakdown  
Bend test at 200 g,  $\pm$ 90 °, 30 cycles /min: 15,000 cycle minimum



REVISION	DATE	DESCRIPTION
A	9/30/2015	Initial release
A1	1/13/2016	Updated notes, corrected tolerances
A2	1/17/2019	Changed filler material to generic name

PREPARED:  
**AG**  
Digitally signed by AG  
Date: 2019.01.18  
11:27:56 -08'00'

VERIFIED:  
**GL**  
Digitally signed by GL  
Date: 2019.01.18  
12:23:56 -08'00'

DIMENSIONS ARE IN MILLIMETERS

TOLERANCES:  
X:  $\pm$  0.5 mm  
X.X:  $\pm$  0.3 mm  
X.XX:  $\pm$  0.05 mm

NOTES  
RoHS and REACH compliant  
Jacket meets ISO 10993 Biological Compatibility  
Phthalate and halogen free  
Function test: no open, no short, no intermittent

DESCRIPTION:  
Wire, 2C TS, 28 AWG, 150V, 70C, 2.6 mm, spiral shield, TPU

**TENSILITY**

20802 Sockeye Place #130  
Bend, OR 97701 USA  
tel 541.323.3228 fax 541.323.4202  
800 877.670.7118 www.tensility.com

SIZE A	PART NUMBER 30-00653
SCALE: 20:1	SHEET 1 OF 1