2-1986711-5 ACTIVE

Buchanan

TE Internal #: 2-1986711-5

PCB Terminal Blocks, Header, Wire-to-Board, 25 Position, .197 in [5 mm] Centerline, 2 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire

Size

View on TE.com >



Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Number of Positions: 25

Centerline (Pitch): 5 mm [.197 in]

Number of Rows: 2

Features

Product Type Features

Wire Protection

Terminal Block Connector Type	Header			
Connector System	Wire-to-Board			
Connector & Contact Terminates To	Printed Circuit Board			
Configuration Features				
Wire Entry Location	Side			
Stacking Configuration	Side Stackable			
Number of Positions	25			
Number of Rows	2			
Wire Entry Angle	90°			
Electrical Characteristics				
Operating Voltage	300 VAC			
Body Features				

With

White

Lever Color



Primary Product Color	Green
Product Orientation	Vertical
Contact Features	
Contact Mating Area Length	3.5 mm[.138 in]
Contact Mating Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	16 A
Termination Features	
Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Method to Wire & Cable	Push-in
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyamide
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Wire Size	$.05 - 3 \text{ mm}^2$
Usage Conditions	
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Quantity	25

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)



Candidate List Declared Against: JUNE
2022 (224)

Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought













Documents

Product Drawings

SCREWLESS, SW,25P,5.0 PCB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1986711-5_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1986711-5_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1986711-5_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals

VDE Certificate

English