



注記
NOTES

- 1. 材料および仕上げ(めっき仕様) : TABLE 1 参照
MATERIAL AND FINISHES : SEE TABLE 1
- 2. 適合製品及び各種仕様書は下記参照のこと
REFER TO BELOW TABLE ABOUT RELATED PRODUCTS AND VARIOUS SPECIFICATIONS.

適合製品及び各種仕様書
APPLICABLE PRODUCTS AND VARIOUS SPECIFICATIONS

適合ハウジング APPLICABLE HOUSING	212132 SERIES
適合嵌合相手 MATE WITH	212134 SERIES
製品仕様書 PRODUCT SPECIFICATION	2121320000-PS/PS/000
梱包仕様書 PACKING SPECIFICATION	2040179200-SPK/PS/000
コネクタ取扱説明書 APPLICATION SPECIFICATION	2166940000-AS/PS/0000

製品嵌合図は嵌合相手図面参照のこと
MATING VIEW: REFER TO "MATE WITH" PART DRAWING.

1 TABLE 1

部品 PART	材質 MATERIAL	
ターミナル TERMINAL	銅合金 COPPER ALLOY	
	下地めっき UNDER PLATING	ニッケルめっき(下地) : 0.5 micro-meters MIN NICKEL (UNDER PLATING)
	接点部 CONTACT	金めっき : 0.1 micro-meters MIN GOLD PLATING

∅0.6 - 0.7 mm	AWG #28-30	リール REEL	2040175021	連鎖状 CHAIN
絶縁被覆外径範囲 INS. RANGE	適合電線範囲 WIRE RANGE	梱包形態 PACKAGING	発注番号 ORDER No.	端子形状 FORM

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS mm	SCALE NTS	CURRENT REV DESC:		molex		
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 643659				
ANGULAR TOL	± 3.0 °	DRWN: SNAKAMURA08 2019/06/04		PRODUCT CUSTOMER DRAWING		
4 PLACES	± 0.2	CHK'D: SAKIYAMA 2020/09/17		DOCUMENT NUMBER		
3 PLACES	± 0.2	APPR: KOMURAKAMI 2020/09/17		2040175001-SD		
2 PLACES	± 0.2	INITIAL REVISION:		DOC TYPE	DOC PART	REVISION
1 PLACE	± 0.2	DRWN: SNAKAMURA08 2019/06/04		PSD	000	A
0 PLACES	± 0.2	APPR: KOMURAKAMI 2020/09/17		SHEET NUMBER		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER
			A3-SIZE	204017	SEE TABLE	GENERAL